Water Power Development.¹

By PROF. A. H. GIBSON, D.Sc.

THE extent to which the water powers of the world have been investigated and developed during the past decade forms one of the striking engineering features of the period. Although falling or flowing water formed the earliest of the natural sources of energy to be utilised for industrial purposes, it is of interest to note that two-thirds of the water power at present in use has been developed within the last ten years.

The urgent demand for energy to supply the abnormal requirements of the war period, combined with the world shortage of fuel, was responsible for an unprecedented rate of development in most countries with available water-power resources, and especially in those countries normally dependent on imported fuel.

World's Available Water Power.—During the past few years much attention has been paid to statistics of available and developed water powers, and it appears that the available horse-power of the world is of the order of two hundred millions, of which approximately twenty-five millions is at present developed or is in course of development.

Power Available in Great Britain and in the British Empire.—With the noteworthy exceptions of Canada and New Zealand, practically nothing had been done, prior to 1915, by any part of the British Empire to develop or even systematically to investigate the possibilities of developing its water powers. It is true that a number of large installations had been constructed in India and Tasmania, but their aggregate output was relatively inconsiderable.

Since then, however, there has been a general tendency to initiate such investigations, and at the present time these are being carried out with varying degrees of thoroughness in India, Ceylon, Australia, South and East Africa, and British Guiana. While it is known that there is ample water power in Newfoundland, Nigeria, Rhodesia, Papua, and the Gold Coast, no very definite information is available, nor are any steps apparently being taken to obtain data in these countries.

The Water-power Committee of the Conjoint Board of Scientific Societies, which has been studying the state of investigation and development throughout the Empire since 1917, has, however, come to the conclusion that its total available water-power resources are at least equivalent to between fifty and seventy million horse-power.

Of the developed power in the Empire about 80 per cent. is in Canada. Throughout the remainder of its territories only about 700,000 horse-power is as yet developed, or only a little more than 1 per cent. of the power available, a figure which compares with about 24 per cent. for the whole of Europe, and 21 per cent. for North

America, including Canada and the U.S.A. These figures sufficiently indicate the relatively large scope for future development.

With a view of ascertaining the resources of our own islands, a Board of Trade Water-power Resources Committee was appointed in 1918. This Committee, which has just presented its final report, has carried out preliminary surveys of as many of the more promising sites as its limited funds allowed, and has obtained data from the Board of Agriculture for Scotland, the Ordnance Survey Department, the Ministry of Munitions, and from civil engineers in private practice, regarding a large number of other sites.

As might be anticipated, Scotland, with its comparatively high rainfall, mountainous area, and natural lochs, possesses relatively greater possibilities than the remainder of the United Kingdom, and investigation has shown that it offers a number of comparatively large schemes. Nine of the more immediately promising of those examined by the Committee have an average output ranging from 7000 to 40,000 continuous 24-hour horse-power, and an aggregate capacity of 183,000 horse-power, while in every case the estimated cost of construction is such that power could be developed at a cost appreciably lower than from a coal-fired station built and operated under present-day conditions. The aggregate output of the Scottish schemes brought before the notice of the Committee, some of which, however, are not commercially feasible at the moment, is roughly 270,000 continuous horse-power.

In addition to these there are a very large number of other small schemes which have not yet been investigated,² and it is probably well within the mark to say that there are water-power sites in the country capable of developing the equivalent of 400,000 continuous horse-power, or 1,500,000 horse-power over a normal working week, at least as cheaply as from a coal-fired installation.

A number of attractive schemes are also available in North Wales, though these are in general more expensive than those in Scotland.

Owing to the general flatness of the gradients, there are, except possibly around Dartmoor, no schemes of any large individual magnitude in England, but there are a large number of powers ranging from 100 to 1000 horse-power which might be developed from river flow uncontrolled by storage.

Investigations on a few typical watersheds throughout England and Wales appear to show that the possible output averages approximately eight continuous horse-power per square mile of catchment area, which would be equivalent to an

¹ Abridged from the presidential address delivered to Section G (Engineering) of the British Association at Edinburgh on September 9.

² In a paper read before the Royal Society of Arts on January 25, 1918, Mr. A. Newlands gave a list of 122 potential Scottish schemes, the capacity of which he estimated, on a very conservative basis, at 375,000 horse-power.

aggregate of about 450,000 horse-power. Although much of this potential output is not commercially feasible, it would give the equivalent of 500,000 horse-power over a normal working week if only 30 per cent. of it were fully utilised.

In the report recently issued by the Irish Sub-Committee of the Board of Trade Water-power Committee it is estimated that approximately 500,000 continuous 24-hour horse-power is commercially available in Ireland, and that if utilised over a 48-hour working week, its capacity would be at least seven times as great as that of the engine power at present installed in the country for industrial purposes.

It appears then that, although the water-power possibilities of the United Kingdom are small in comparison with those of some more favoured countries, they are by no means so negligible as is commonly supposed, even in comparison with the present industrial steam-power resources of the country.

The capacity of the fuel-power plants installed for industrial and public utility services in the United Kingdom in 1907 was approximately 9.8 million horse-power. Allowing for an increase of 15 per cent. since then, and an average load factor of 35 per cent., this is equivalent to 32,000 million horse-power hours per annum, or to a continuous 24-hour output of only 3.7 million horse-power.

According to Sir Dugald Clerk, the average consumption of coal per horse-power hour in this country is about 3.9 lb., which, on the above basis, would involve a total annual consumption of fifty-five million tons for industrial purposes, not including railways or steamships.

Adopting this figure of 32,000 million horse-power hours as the annual demand for power for industrial purposes, it appears that the inland water-power resources of the United Kingdom are capable of supplying about 27 per cent. of this, a proportion which, in such an industrial country as our own, is somewhat surprisingly large.

Many of the small powers would be well adapted for linking up, as automatic or semi-automatic stations, into a general network of electricity supply, or for augmenting the output of municipal supply works, as has been done so successfully, for example, at Chester, Worcester, and Salisbury.

The development of the many small schemes available in the Scottish Highlands would probably have a great effect on the social life of the community. It would go far towards reviving and extending those small local industries which should form an essential feature of the ideal rural township. Commercially such undertakings may appear to be of small importance, but as a factor in promoting the welfare of the State, economical and political, their influence can hardly be overestimated.

Some of the larger schemes in Scotland would lend themselves admirably to transmission to its industrial districts, while others, in close vicinity to the sea-board, would appear to be well adapted

for supplying chemical, or electro-physical, or metallurgical processes.

Conservation.—The importance of water-power development from the point of view of conservation of natural resources requires no emphasis. When the value of coal purely as a chemical asset, or as a factor in the manufacture of such materials as iron and steel, cement, etc., is considered, its use as a fuel for power purposes, when any other equally cheap source of energy is available, would appear, indeed, to be unjustifiable.

The consumption of coal in the best modern steam plant of large size, giving continuous output, would be about nine tons per horse-power year, and on this basis the world's available water power if utilised would be equivalent to some 1,800,000,000 tons of coal per annum. The world's output of coal in 1913 was approximately 1,200,000,000 tons, of which about 500,000,000 tons were used for industrial power purposes, so that on this basis 55,000,000 continuous water horse-power would be equivalent to the world's industrial energy at that date.

Not only does the use of water power lead to a direct conservation of fuel resources, but it also serves to a notable degree to conserve man power. To take an extreme example, each of the 40,000 horse-power units now being installed at Niagara Falls will require for operation two men per shift. It is estimated that to produce the same power from a series of small factory steam plants, more than eight hundred men would be required to mine, hoist, screen, load, transport by rail, unload, and fire under boilers the coal required, while, if account be taken of the additional labour involved in horse transport, wear and tear of roads and of railroad tracks and rolling stock, the number would be considerably increased.

Uses of Hydro-Electric Energy.—While a large proportion of the energy developed from water power is utilised for industrial purposes and for lighting, power, and traction, an increasing proportion is being used for electro-chemical and electro-metallurgical processes.

In Norway the electro-chemical industry absorbed 770,000 horse-power in 1918, or approximately 75 per cent. of the total output, as compared with 1500 horse-power in 1910. Of this some 400,000 horse-power was utilised in nitrogen fixation alone.

The production of electric steel in the U.S.A. increased from 13,700 tons in 1909 to 24,000 tons in 1914, and to 511,000 tons in 1918, this latter quantity absorbing 300 million kw. hours, equivalent to almost 400,000 continuous horse-power.

In Canada, in 1918, the pulp and paper industry absorbed 450,000 horse-power, or 20 per cent. of the total, while the output of central electric stations amounted to 70 per cent. of the total.

The electrification, on a large scale, of trunk line railways is also a probability in the not distant future. In the U.S.A. 650 miles of the main line of the Chicago, Milwaukee, and St. Paul Railway, comprising 850 miles of track, have been electrified, the power for operation being

obtained from hydro-electric stations. In France much of the track of the Compagnie du Midi in the region of the Pyrenees has been electrified with the aid of water power; much of the Swiss railway system has been electrified; and the electrification of many other trunk lines on the European continent is at present under consideration.

Quite apart from the probable huge demand in the distant future for energy for the manufacture of artificial fertilisers by some system of nitrogen fixation, agriculture would appear to offer a promising field for the use of hydro-electric power.

Much energy is now being utilised in the U.S.A. for purely agricultural purposes. In California, for example, there is in effect one vast system of electrical supply extending over a distance of 800 miles with 7200 miles of high-tension transmission lines. This is fed from seventy-five hydro-electric stations, inter-connected with forty-seven steam plants, to give a total output of 785,000 horse-power. A further group of thirteen hydro-electric schemes now under construction will add another 520,000 horse-power. A large proportion of this power is used in agriculture, and a census in 1915 showed that electric motors equivalent to more than 190,000 horse-power were installed on Californian farms. The Californian rice industry is almost wholly dependent on irrigation made possible by electric pumping, while most of the mechanical processes involved in farming are being performed by electric power.

There can be little doubt that the economic development of many of our tropical dependencies is bound up in the development of their water-power resources. Not only would this enable railroads to be operated, irrigation schemes to be developed, and mineral deposits to be mined and worked, but it would also go far to solve the black labour problem, which promises to be one of some difficulty in the near future.

While those outlets for electrical energy which are now in sight promise to absorb all the energy which can be cheaply developed for many years to come, there are many other probable directions in which cheap energy would find a new and profitable outlet. Among these may be mentioned the purification of municipal water supplies, the sterilisation of sewage, the dehydration of food products, and the preservation of timber.

Research in Hydro-Electric Problems.—There are few branches of engineering in which research is more urgently required and in which it might be more directly useful.

Among the many questions still requiring investigation on the civil and mechanical side may be mentioned:—

1. *Turbines.*—Investigation of turbine corrosion as affected by the material and shape of the vanes.

Effect of erosion due to sand and silt.

Resistance to erosion offered by different materials and coatings.

Bucket design in low head high-speed turbines.

Draft tube design.

Investigation of the directions and velocities of flow in modern types of high-speed turbines.

Investigation of the degree of guidance as affected by the number of guide and runner vanes.

2. *Conduits and Pressure Tunnels.*—The design of large pipe lines under low heads with the view of reducing the weight of metal. The investigation of anti-corrosive coatings, so as to reduce the necessity for additional wall thickness to allow for corrosion.

Methods of strengthening large thin-walled pipes against bending and against external pressures.

Methods of lining open canals and of boring and lining pressure tunnels.

Effects of curvature in a canal or tunnel.

3. *Dams.*—Most efficient methods of construction and best form of section especially for rock-fill and earthen dams. Best methods of producing water tightness.

4. *Run-off Data.*—Since the possibility of designing an installation to develop the available power efficiently and economically depends in many cases essentially on the accuracy of the run-off data available, the possession of accurate data extending over a long series of years is of great value.

While such data may be obtained either from stream gaugings or from rainfall and evaporation records, the former method is by far the more reliable. For a reasonable degree of accuracy, however, records must be available extending over a long period of years, and at the present moment such data are available only in very few cases.

Where accurate rainfall and evaporation records are available, it is possible to obtain what is often a sufficiently close approximation to the run-off, but even rainfall records are not generally at hand where they are most required, and even in a district where such records are available, they are usually confined to easily accessible points, and are seldom extended to the higher levels of a catchment area where the rainfall is greatest. Even throughout the United Kingdom our knowledge of the rainfall at elevations exceeding 500 ft. is not satisfactory, and little definite is known concerning that at elevations exceeding 1000 ft.

In this country evaporation may account for between 20 and 50 per cent. of the annual rainfall, depending on the physical characteristics of the site, its exposure, mean temperature, and the type of surface covering. In some countries evaporation may account for anything up to 100 per cent. of the rainfall. As yet, however, few records are available as to the effect of the many variables involved. An investigation devoted to the question of evaporation from water surfaces, and from surfaces covered with bare soil and with various crops, under different conditions of wind, exposure, and mean temperature, would appear to be urgently needed. If this could be combined with an extension of Vermeulle's investigation into the relationship between rainfall, evaporation, and run-off on watersheds of a few characteristic types, it would do much towards enabling an accu-

rate estimate of the water-power possibilities of any given site to be predetermined.

Even more useful results would follow the initiation of a systematic scheme of gauging applied to all streams affording potential power sites.

Tidal Power.—The question of tidal power has received much attention during the last few years. In this country it has been considered by the Water-power Resources Committee of the Board of Trade, which has issued a special tidal power report dealing more particularly with a suggested scheme on the Severn. The outline of a specific scheme on the same estuary was published by the Ministry of Transport towards the end of 1920.

In France a special commission has been appointed by the Ministry of Public Works to consider the development of tidal power, and it has been decided to erect a 3000 kw. experimental plant on the coast of Brittany. With the view of encouraging research the Government proposes to grant concessions, where required, for the laying down of additional installations.

The tidal rise and fall around our coasts represents an enormous amount of energy, as may be exemplified by the fact that the power obtainable from the suggested Severn installation alone, for a period of eight hours daily throughout the year, would be of the order of 450,000 horse-power.

Many suggestions for utilising the tides by the use of current motors, float-operated air compressors, and the like have been made, but the only practicable means of utilising tidal energy on any large scale would appear to involve the provision of one or more dams, impounding the water in tidal basins, and the use of the impounded water to drive turbines.

The energy thus rendered available is, however, intermittent; the average working head is low and varies daily within very wide limits, while the maximum daily output varies widely as between spring and neap tides.

If some electro-chemical or electro-physical process were available, capable of utilising an intermittent energy supply subject to variations of this kind, the value of tidal power would be greatly increased. At the moment, however, no such process is commercially available, and in order to utilise any isolated tidal scheme for normal industrial application it is necessary to provide means for converting the variable output into a continuous supply constant throughout the normal working period.

Various schemes have been suggested for obtaining a continuous output by the co-ordinated operation of two or more tidal basins separated from each other and from the sea by dams with appropriate sluice gates. This method, however, can get over the difficulty of equalising the outputs of spring and neap tides only if it be arranged that the maximum rate of output is that governed by the working head at the lowest neap tide, in which case only a small fraction of the available energy is utilised.

When a single tidal basin is used it is necessary

to provide some storage system to absorb a portion of the energy during the daily and fortnightly periods of maximum output, and for this purpose the most promising method at the moment appears to involve the use of an auxiliary high-level reservoir into which water is pumped when excess energy is available, to be used to drive secondary turbines as required. It is, however, possible that better methods may be devised. Storage by the use of electrically heated boilers has been suggested, and the whole field of storage is one which would probably well repay investigation.

If a sufficiently extensive electrical network were available, linking up a number of large steam and inland water power stations, a tidal power scheme might readily be connected into such a network without any storage being necessary, and this would appear to be a possibility which should not be overlooked in the case of our own country.

Investigation necessary.—A tidal power project on any large scale involves a number of special problems for the satisfactory solution of which our present data are inadequate.

Thus the effect of a barrage on the silting of a large estuary, and the exact effect on the level in the estuary and in the tidal basin at any given time can only be determined by experiment, either on a small installation, or preferably on a model of the large scheme.

Many of the hydraulic, mechanical, and electrical problems involved are comparatively new, and there is little practical experience to serve as a basis for their solution.

Among these may be mentioned:—

1. The most advantageous cycle of operations as regards working periods, mean head, and variations of head.
2. The methods of control and of sluice-gate operation.
3. Effect of changes of level due to wind or waves.
4. The best form of turbine and setting and the most economical turbine capacity.
5. The possibilities of undue corrosion of turbine parts in salt water.
6. The best method of operation; constant or variable speed.
7. Whether the generators shall be geared or direct driven.
8. Whether generation shall be by direct or alternating current.

The questions of interference with navigation and with fisheries, of utilising the dam for rail or road transport across the estuary, and, above all, economic questions connected with the cost of production, and the disposal of the output of such an installation, also require the most careful consideration before a scheme of any magnitude can be embarked upon with assurance of success.

In view of the magnitude of the interests involved, and of the fact that rough preliminary estimates indicate that to-day current even for an ordinary industrial load could be supplied from such an installation at a price lower than from a steam generating station giving the same output

with coal at its present price, it would appear desirable that these problems should receive adequate investigation at an early date.

Facilities for Research in Hydraulic and Cognate Problems.—In view of the considerations already outlined, and especially in view of the large part which British engineering will probably play in future water-power developments, the provision on an adequate scale at some institution in this country of facilities for research on hydraulic and cognate problems connected with the development of water power is worthy of serious attention.

At present the subject is treated in the curriculum of the engineering schools of one or two of our universities, but in no case is the laboratory equipment really adequate for the purpose in question.

What is required is a research laboratory with facilities for experiments on the flow of water on a fairly large scale; for carrying out turbine tests on models of sufficient capacity to serve as a basis for design; and, if possible, working in conjunction with one or more of the hydro-electric stations

already in existence, or to be installed in the country, at which certain large-scale work might be carried out.

The provision of such a laboratory is at present under consideration in the United States, and in view of the rapidity with which the designs of hydraulic prime movers and their accessories are being improved at the moment, it would appear most desirable that the British designer, in order that the deservedly high status of his products should be maintained and enhanced, should at least have access to equal facilities, and, if necessary, be able to submit any outstanding problems to investigation by a specially trained staff.

The extent to which our various heat engine laboratories have been able of recent years to assist in the development of the internal combustion engine, and to which our experimental tanks have assisted in the development of the ship-building industry, is well known to most of us, and the provision of similar facilities to assist in the development of our hydro-electric industry would probably have equally good results in this connection.

The Danish Deep Sea Expedition.

THE Danish Deep Sea Expedition, which left Copenhagen on August 30 on board the new research steamer *Dana*, is expected to spend about ten months in the temperate and tropical parts of the North Atlantic. The object of the expedition is to carry out deep sea investigations in accordance with a scheme which was submitted

for the Study of the Sea" and of several other Danish men of science interested in oceanography. The president is Commander C. F. Drechsel, and the vice-president Vice-Admiral C. F. Wandel (leader of the Danish Ingolf Expedition in 1895-96). Admiral H.R.H. Prince Valdemar of Denmark is patron of the expedition. The ex-

penses are being defrayed by funds supplied by various private persons and by the Danish Government annual grants for marine investigations in connection with the International Council for the Exploration of the Sea.

The ship of the expedition, the *Dana* (Fig. 1), of the Lord Mersey trawler type, was bought in England by the Danish Government to replace the old research steamer *Thor*, which was sold some years ago. The *Dana* has been equipped for marine research work at the Royal Dockyard, Copenhagen. She has a length of about 140 ft. between perpendiculars, and is 325 tons gross register. She carries a 600-h.p. triple expansion engine, giving her a speed of 9 knots. A large

deck-house has been constructed, which contains two laboratories—a larger biological laboratory with accommodation for five workers, and a smaller one for hydrographical work with room for two—together with a mess-room for the scientific staff, and a cabin for the

FIG. 1.—S.S. *Dana*.

by the leader of the expedition, Dr. Johs. Schmidt, to the International Council for the Exploration of the Sea during their meeting at Copenhagen in July last.

The committee of the expedition consists of the members of the official Danish "Committee