the error resulting in $I'(000)$ may be very large. This uncertain correction of the temperature effect constitutes the chief source of errors in the value deduced for $I'(000)$.

(4) The correct choice of n_1, n_2, n_3 . The strict condition is

$$d_m \geq \frac{1.2a}{n_1}, \frac{1.2b}{n_2}, \frac{1.2c}{n_3},$$

where d_m denotes the shortest interatomic distance between any two atoms in contact in the crystal. Because this condition is rather too strict to be satisfied easily, let us introduce a much more approximate condition,

$$\begin{aligned} d_a &\geq 1.2 \left\{ \left(\frac{a}{n_1} \right)^2 + \left(\frac{b}{n_2} \right)^2 + \frac{2ab}{n_1 n_2} |\cos \gamma| \right\}^{1/2}, \\ 1.2 \left\{ \left(\frac{b}{n_2} \right)^2 + \left(\frac{c}{n_3} \right)^2 + \frac{2bc}{n_2 n_3} |\cos \alpha| \right\}^{1/2}, \\ 1.2 \left\{ \left(\frac{a}{n_1} \right)^2 + \left(\frac{c}{n_3} \right)^2 + \frac{2ac}{n_1 n_3} |\cos \beta| \right\}^{1/2}, \end{aligned}$$

where d_a denotes the average interatomic distance between any two contact atoms in the crystal: d_a can be roughly estimated from the nature of the atoms contained. In case the structure contains a number of very heavy small atoms, their effect on $I'(000)$ can be estimated.

When all of the foregoing four points have been provided for, it is believed that the error in $I'(000)$ would fall in the range of 5–20 per cent in the usual cases.

To illustrate the use of (3), let us first take a crystal consisting of only one atom at the origin in the unit cell, the number of electrons in the shell of the atom being Z and the atomic structure factor, $f(hkl)$. Then $F(hkl) = f(hkl) = Z\bar{f}(hkl)$. $F^2(000) = Z^2$. If we assume $I'(hkl) = F^2(hkl)$, we have $I'(hkl)/\bar{f}^2(hkl) = Z^2$. Substituting these values in (3) we obtain

$$I'(000) = \frac{\sum_{h=-\infty}^{\infty} U_{nh} \left(\sum_{k=-\infty}^{\infty} U_{nk} \right) \left(\sum_{l=-\infty}^{\infty} U_{nl} \right) - U_{n,0} U_{n,0} U_{n,0}}{1 - U_{n,0} U_{n,0} U_{n,0}}.$$

Using U_{nh} given in the table, with $n_1 = 48, n_2 = 32, n_3 = 16$, we obtain $I'(000) = 1.0051Z^2$, which differs from the assumed $I'(000) = F^2(000) = Z^2$ only by 0.51 per cent. The choice of U_{nh} of any other n_1, n_2, n_3 will give similar results.

Let us next illustrate the method by studying a real crystal, say, *paradinitrobenzene*, the structure of which was determined carefully by James, King and Horrocks⁴, who made the determination on the basis of intensities of reflexions $h0l, h0l$ and $0kl$. Strictly speaking, we should determine $I'(000)$ from equation (3), based on the relative intensities of the whole set of reflexions hkl . But in the case of the present structure, as we know already from James, King and Horrocks' paper that there is no overlapping of atoms directly upon each other in the projection of the structure in direction b to the ac plane (see ref. 4, Fig. 3), a study of the relative intensities of reflexions $h0l$ is sufficient for our purpose of illustration. Then let us take their observed $F^2(h0l)$ directly as our $I'(h0l)$ and take Robertson's f -values⁵ directly as our $\bar{f}(h0l)$. Since no further temperature correction has been made, the values of $\bar{f}(h0l)$ so obtained are under-corrected for the temperature effect as revealed

from my studies of the same structure. But we may deliberately use such rough values of $\bar{f}(hkl)$ in order to see if $I'(000)$ so deduced still proves reliable. The structure has

$$F^2(000) = 164^2, \sum_{i=1}^t Z_i^2 = 1140$$

when the contribution of the hydrogen atoms is neglected. $h_M = 13$ such as in $h0l = 13\ 0\ 1$, and $l_M = 7$ such as in $h0l = 1\ 0\ 7$. Accordingly, we take $n_1 = 24, n_2 = 12$. The two-dimensional equation for $I'(000)$ is given by

$$I'(000) = F^2(000) \frac{\sum' U_{nh} U_{n_2} I'(h0l) [\bar{f}^2(h^*l^*)]}{\sum_{i=1}^t Z_i^2 - U_{n,0} U_{n,0} F^2(000)}. \quad (3a)$$

where $\sum'$ denotes $\sum_{h=-\infty}^{\infty} \sum_{l=-\infty}^{\infty}$,

excluding the term with $h=l=0$. Substituting in (3a) the appropriate U_{nh} from the table and the other quantities mentioned above, we obtain $I'(000) = 0.85F^2(000)$, differing from the assumed $I'(000) = F^2(000)$ by 15 per cent; an acceptable error obtained by deliberately choosing rather rough values of $\bar{f}(hkl)$.

Details of this work, including the method of correcting for the effect of small heavy atoms, will be presented elsewhere.

¹ Booth, A. D., *Nature*, **158**, 380 (1946). Boyes-Watson, J., Davidson, E., and Perutz, M. F., *Proc. Roy. Soc., A*, **191**, 83 (1947). Harker, D., and Kasper, J. S., Reports of 1947 summer meeting of ASEXRD, 13. Buerger, M. J., *Phys. Rev.*, **73**, 927 (1948).

² Booth, A. D., Kasper, J. S., Reports of 1947 summer meeting of ASEXRD, 14.

³ Yü, S. H., *Nature*, **150**, 151 (1942).

⁴ James, R. W., King, G., and Horrocks, H., *Proc. Roy. Soc., A*, **153**, 878 (1935).

⁵ Robertson, J. M., *Proc. Roy. Soc., A*, **150**, 109 (1935).

FRACTURE OF SOLIDS

A CONFERENCE on "The Fracture of Solids" was held by the British Rheologists' Club on October 29. Prof. N. F. Mott, recently elected president of the Club, opened the conference by pointing out that, quite apart from its practical importance, fracture was the most interesting property of solids to the theoreticians because it is the least understood property, no progress having been made beyond the Griffith crack-theory of 1924. It is not known how cracks exist nor what causes them; experimental work has made clear what happens during fracture, but not how it occurs.

Dr. C. F. Tipper then presented a paper describing some beautiful experimental work on the subject of fracture in mild steel. She divided fracture into three types: the first corresponds to a parting along a shear plane; the second along two intersecting planes, giving a wedge-shaped fracture; and the third along a plane quite different from the shear plane, often at right angles to the principal tensile stress. Iron and mild steel show all three types of fracture, and it is possible to have all in the same test-piece, even in adjacent crystals. The amount of energy absorbed in fracture depends on how much of each type goes to make up the total fracture. The third type, which is generally brittle, can always be

traced back to a notch, and so in laboratory experiments a notch is inserted deliberately. The metal at the base of the notch can be regarded as a tensile specimen of very short gauge-length eccentrically loaded, and the natural crack is thus started at 90° to the direction of loading. In a very ductile material the crack eventually turns to 45°, and in a brittle material its mean path remains perpendicular to the direction of loading.

Dr. Tipper showed the importance of inclusions in the metal, separation occurring around such inclusions at an early stage in the deformation and forming a pattern of holes near the actual fracture. This separation divides the material into a bundle of independent test-pieces. Inclusions can also stop a fracture when they lie at right angles to the direction of propagation, as they then relieve the stress. Fracture is thus very strongly structure-sensitive. The main conclusion of this work is that fracture begins piecemeal at different places in the material, a fact confirmed by the work of Bridgman, in which a high hydrostatic pressure is found to increase ductility. In the processes of rolling and wire drawing, cracks are not allowed to open, and this is why such large strains are possible without fracture.

Prof. H. Moore then spoke on the fracture of glass. He pointed out that the phenomena of fracture should be explainable in terms of structure, but that a theory of structure could not be based on a study of fracture alone, as had been attempted by some workers. Vitreous silica consists of SiO_2 tetrahedra linked by the oxygens at the corners, each tetrahedron having four linkages at 120° to each other. In silicate glasses the introduction of an alkali such as sodium oxide breaks these linkages, but divalent oxides, such as lime, can provide bridges between tetrahedra which have become temporarily separated. On the molecular scale the structure is irregular, but on any larger scale it is isotropic, giving rise to the familiar conchoidal type of fracture. The structure has no slip planes, and if strained so that one linkage is broken, the other neighbouring linkages, inclined at 120° to the broken link, are also disrupted. Glass has therefore no ductility, its yield strength being equal to its breaking strength.

As with metals, the strength calculated from the structure is many thousand times greater than the observed strength. Fine freshly drawn glass fibres are, however, many hundred times stronger than massive glass; but the strength diminishes extremely rapidly in moist air. The weakness of glass is in its surface, and can be accounted for by the Griffith surface-flaw theory in combination with the effects produced by adsorbed moisture. Moisture rapidly alters the surface layers and can, in fact, cause the whole of the skin to peel off. Under continuous steady loading in moist air, glass is weaker than under momentary loading, due to progressive deterioration of the side-surfaces of the flaws opened by the deformation. This is not a fatigue effect similar to the fatigue effects in metals; under continually reversed loading, glass shows no sign of fatigue because its structure is not affected by the strain reversals.

Mr. H. Warburton Hall then spoke of the fracture of plastics. The understanding of fracture is likely to be easier in the case of the thermo-plastic types than in the case of the more heterogeneous thermosetting plastics. A large amount of experimental data on the mechanical behaviour of the former have been obtained, including investigations into the dependence

of tensile strength on such fundamental properties as molecular weight, molecular weight distribution, chemical structure of the polymer, crystallinity, molecular orientation, time of stressing, etc. Haward found that the time to fail of cellulose acetate under constant stress was independent of any rest or deformation-recovery periods allowed during the test, and depended only on the total time under stress; thus in this case all stressing does irreparable damage.

Mr. Hall described investigations on methyl methacrylate at the Royal Aircraft Establishment which had confirmed that tensile stress combined with solvent vapour absorption caused crazing, and that crazing consists of fractures in the surface of the material. The fractures are local tensile failures which under continued stressing lead to bulk failure. There are, however, two main conditions of the material which influence its tendency to craze. (1) Condition direct from the casting process: the material then contains residual solvent (namely, monomer) and elastic strains. If either the solvent content or the condition of elastic strain is increased, crazing will result. In this case solvent vapour causes random pattern crazing. (2) Heat-treated condition: in this case the residual monomer is fully polymerized, the elastic strains are eliminated and *both* solvent vapour and tensile stress are needed to cause crazing. The craze lines, however, are now always perpendicular to the direction of the tensile stress.

A large number of liquids have been investigated, and all those which swell or dissolve the polymer tend to cause crazing.

Finally, Mr. Hall mentioned that the detailed investigations by E. W. Russell on the solvent-vapour absorption characteristics of methyl methacrylate had indicated the possible mechanism of crazing. His results show that films of the polymer stretched at high temperatures and then cooled to normal temperatures while stretched, absorb vapour more rapidly than films not so stretched. It is likely, therefore, that crazing is due to non-uniform vapour absorption which causes stress relaxation at one point, resulting in stress concentration at others, until local rupture takes place, which appears as crazing.

Dr. E. Orowan spoke on the theory of fracture, pointing out that the Griffith crack-propagation theory gave a very good account of fracture phenomena in glasses. According to the Griffith formula, the strength should be proportional to the square root of the surface energy; according to experiments by Obreimow and himself, the surface energy of mica is about twelve times higher in vacuum than in air, and, if this ratio is assumed for glasses, the strength in vacuum should be about $\sqrt{12}$ (or 3.5) times higher than the strength in air. The same ratio should exist between the fracture stresses for very short and very long durations of the test, because the air cannot penetrate to the tip of the crack in the first case; moreover, there should be no difference between long-time strength and short-time strength if the experiment is carried out in vacuum. All these conclusions have been confirmed experimentally. Dr. Orowan pointed out the geometrical meaning of the two-dimensional fracture criterion put forward by Griffith in 1924. If the two principal stresses P and Q are plotted as ordinates, the criterion of fracture is represented in the plane of P — Q by a curve consisting of a parabola, with vertex at the origin and axes directed at 45° into the negative quadrant, and

traced back to a notch, and so in laboratory experiments a notch is inserted deliberately. The metal at the base of the notch can be regarded as a tensile specimen of very short gauge-length eccentrically loaded, and the natural crack is thus started at 90° to the direction of loading. In a very ductile material the crack eventually turns to 45°, and in a brittle material its mean path remains perpendicular to the direction of loading.

Dr. Tipper showed the importance of inclusions in the metal, separation occurring around such inclusions at an early stage in the deformation and forming a pattern of holes near the actual fracture. This separation divides the material into a bundle of independent test-pieces. Inclusions can also stop a fracture when they lie at right angles to the direction of propagation, as they then relieve the stress. Fracture is thus very strongly structure-sensitive. The main conclusion of this work is that fracture begins piecemeal at different places in the material, a fact confirmed by the work of Bridgman, in which a high hydrostatic pressure is found to increase ductility. In the processes of rolling and wire drawing, cracks are not allowed to open, and this is why such large strains are possible without fracture.

Prof. H. Moore then spoke on the fracture of glass. He pointed out that the phenomena of fracture should be explainable in terms of structure, but that a theory of structure could not be based on a study of fracture alone, as had been attempted by some workers. Vitreous silica consists of SiO_2 tetrahedra linked by the oxygens at the corners, each tetrahedron having four linkages at 120° to each other. In silicate glasses the introduction of an alkali such as sodium oxide breaks these linkages, but divalent oxides, such as lime, can provide bridges between tetrahedra which have become temporarily separated. On the molecular scale the structure is irregular, but on any larger scale it is isotropic, giving rise to the familiar conchoidal type of fracture. The structure has no slip planes, and if strained so that one linkage is broken, the other neighbouring linkages, inclined at 120° to the broken link, are also disrupted. Glass has therefore no ductility, its yield strength being equal to its breaking strength.

As with metals, the strength calculated from the structure is many thousand times greater than the observed strength. Fine freshly drawn glass fibres are, however, many hundred times stronger than massive glass; but the strength diminishes extremely rapidly in moist air. The weakness of glass is in its surface, and can be accounted for by the Griffith surface-flaw theory in combination with the effects produced by adsorbed moisture. Moisture rapidly alters the surface layers and can, in fact, cause the whole of the skin to peel off. Under continuous steady loading in moist air, glass is weaker than under momentary loading, due to progressive deterioration of the side-surfaces of the flaws opened by the deformation. This is not a fatigue effect similar to the fatigue effects in metals; under continually reversed loading, glass shows no sign of fatigue because its structure is not affected by the strain reversals.

Mr. H. Warburton Hall then spoke of the fracture of plastics. The understanding of fracture is likely to be easier in the case of the thermo-plastic types than in the case of the more heterogeneous thermosetting plastics. A large amount of experimental data on the mechanical behaviour of the former have been obtained, including investigations into the dependence

of tensile strength on such fundamental properties as molecular weight, molecular weight distribution, chemical structure of the polymer, crystallinity, molecular orientation, time of stressing, etc. Haward found that the time to fail of cellulose acetate under constant stress was independent of any rest or deformation-recovery periods allowed during the test, and depended only on the total time under stress; thus in this case all stressing does irreparable damage.

Mr. Hall described investigations on methyl methacrylate at the Royal Aircraft Establishment which had confirmed that tensile stress combined with solvent vapour absorption caused crazing, and that crazing consists of fractures in the surface of the material. The fractures are local tensile failures which under continued stressing lead to bulk failure. There are, however, two main conditions of the material which influence its tendency to craze. (1) Condition direct from the casting process: the material then contains residual solvent (namely, monomer) and elastic strains. If either the solvent content or the condition of elastic strain is increased, crazing will result. In this case solvent vapour causes random pattern crazing. (2) Heat-treated condition: in this case the residual monomer is fully polymerized, the elastic strains are eliminated and *both* solvent vapour and tensile stress are needed to cause crazing. The craze lines, however, are now always perpendicular to the direction of the tensile stress.

A large number of liquids have been investigated, and all those which swell or dissolve the polymer tend to cause crazing.

Finally, Mr. Hall mentioned that the detailed investigations by E. W. Russell on the solvent-vapour absorption characteristics of methyl methacrylate had indicated the possible mechanism of crazing. His results show that films of the polymer stretched at high temperatures and then cooled to normal temperatures while stretched, absorb vapour more rapidly than films not so stretched. It is likely, therefore, that crazing is due to non-uniform vapour absorption which causes stress relaxation at one point, resulting in stress concentration at others, until local rupture takes place, which appears as crazing.

Dr. E. Orowan spoke on the theory of fracture, pointing out that the Griffith crack-propagation theory gave a very good account of fracture phenomena in glasses. According to the Griffith formula, the strength should be proportional to the square root of the surface energy; according to experiments by Obreimow and himself, the surface energy of mica is about twelve times higher in vacuum than in air, and, if this ratio is assumed for glasses, the strength in vacuum should be about $\sqrt{12}$ (or 3.5) times higher than the strength in air. The same ratio should exist between the fracture stresses for very short and very long durations of the test, because the air cannot penetrate to the tip of the crack in the first case; moreover, there should be no difference between long-time strength and short-time strength if the experiment is carried out in vacuum. All these conclusions have been confirmed experimentally. Dr. Orowan pointed out the geometrical meaning of the two-dimensional fracture criterion put forward by Griffith in 1924. If the two principal stresses P and Q are plotted as ordinates, the criterion of fracture is represented in the plane of P — Q by a curve consisting of a parabola, with vertex at the origin and axes directed at 45° into the negative quadrant, and

also of the vertical and horizontal tangents to this parabola. He found that this fracture criterion agrees very well with recent experiments of P. W. Bridgman on the fracture of brittle materials under hydrostatic pressures.

In the discussion Dr. R. N. Haward pointed out that over a time-range of $10^7:1$, Preston had found that the relation between $\log T$ and $1/S$ (S is breaking strength) is linear, and he doubted whether this would bend over just at the limits which were set by the experimental conditions to give Dr. Orowan's factor of 3.5.

Mr. R. L. Brown spoke on the fracture of coal, where one is interested in the size distribution of the fragmented pieces and also the variation of strength of these pieces with size. He showed that, when the size distribution of broken coal deviates from the natural distribution, some of the particles can be relatively weak, so that further rough handling of the consignment of coal tends to bring them back to the natural size-distribution. This theoretical investigation is confirmed by experimental evidence on one coal. Mr. Brown pointed out that, in the case of coal, one had to think of millions of particles, and it was not possible to consider an individual test-specimen; accordingly, the strength measurements were made by a shatter test, in which the coal was dropped several feet on to an iron plate, and the strength calculated from the resulting degradation.

Dr. W. W. Barkas spoke on the fracture of wood, the oldest structural material. Under tension, wood fractures by the oxygen groups, and the tensile strength accordingly only goes down by 25 per cent when the wood is wet. On the other hand, under compression, wood fractures by shear on the hydroxyl groups, and the compression strength goes down very much more when the wood is wet. In the manufacture of bent-wood furniture, the bending is therefore by kinking on the inside, the outside remaining unbroken. The work due to fracture is almost independent of the moisture content.

M. W. THRING

AMERICAN INSTITUTE OF BIOLOGICAL SCIENCES

IN discussing recent proposals for an Institute of Biology in Great Britain (see *Nature*, December 4, p. 878), reference was made to the recent establishment and activities of the American Institute of Biological Sciences (A.I.B.S.).

During the Second World War, American biologists became acutely conscious of the fact that the importance of biology and the value of the contributions which biologists were making toward the war effort were little understood by the general public and by Government circles in the United States. As a result of this feeling, a movement developed which finally culminated in the establishment of the American Institute of Biological Sciences. After an informal meeting of a few biologists in Cleveland during September 1944 under the leadership of Prof. E. G. Butler, of Princeton University, an open meeting was called in St. Louis in March 1946 under the sponsorship of the Union of American Biological Societies, the American Biological Society, and the American Society of Naturalists. Dr. Detlev W. Bronk put forward the idea of a biological institute, and those present urged that the informal group con-

tinue its deliberations. As a result, this group presented plans to the Division of Biology and Agriculture of the National Research Council for the formation of an Institute. An advisory committee, with Prof. H. B. Steinbach as executive secretary, drew up a proposed constitution and by-laws. An organising board, consisting of one representative from each biological society affiliated with the Division of Biology and Agriculture of the National Research Council, met on April 11, 1947, adopted the constitution and by-laws, and presented the plans to the several societies for ratification. It was agreed that when ten societies had given their adherence to the Institute it would be formally organised. This was accomplished by January 1948, and on February 20, 1948, representatives of the adhering societies met in Washington and formally constituted the American Institute of Biological Sciences.

The purpose of the Institute as expressed in its constitution is "the advancement of the biological sciences and their applications to human welfare. To serve these purposes, the Institute will, among other things, assist societies and other organisations in such matters of common concern as can be dealt with most effectively by united action; co-operate with local, national and international organisations concerned with the biological sciences; promote unity and effectiveness of effort among all those who are devoting themselves to the biological sciences and their applications by research, teaching, or by study; and foster the relations of the biological sciences to other sciences, to the arts and industries, and to the public good."

The Institute is set up within the framework of the National Research Council. Several categories of membership are provided: (1) member organisations—societies and other non-profit organisations having a national field of operation in the biological sciences; (2) individual members; (3) affiliates—societies wishing to support the Institute in a less active way than through full membership; (4) associates—commercial or other organisations. The Institute is managed by a governing board, consisting of one representative of each member organisation and four representatives of the National Research Council, with a smaller executive committee. The executive officer is designated as the executive secretary. Member societies make annual grants to the Institute in proportion to their membership. Affiliated societies pay 100 dollars or more, and associates pay a minimum of 200 dollars per year. Headquarters of the Institute are in the National Academy of Sciences, National Research Council Building, 2101 Constitution Avenue, Washington, D.C. The chairman of the board of governors is Dr. Ralph E. Cleland; the vice-chairman, Dr. E. G. Butler; and the executive secretary, Dr. Milton O. Lee. Up to the present, fifteen societies have become full members and two societies affiliated members; they are as follow: American Association of Anatomists, American Physiological Society, American Society for Horticultural Science, American Society of Ichthyologists and Herpetologists, American Society of Parasitologists, American Society of Plant Physiologists, American Society of Zoologists, Botanical Society of America, Ecological Society of America, Genetics Society of America, Mycological Society of America, Poultry Science Association, Society for the Study of Development and Growth, Society of American Bacteriologists, American Society of Mammalogists, Society of American Foresters.