GAS CHROMATOGRAPHY

THE annual general meeting of the Gas Chromatography Discussion Group, which is affiliated with the Institute of Petroleum, was held in conjunction with an informal symposium at the Chelsea College of Science and Technology, London, on April 5. The 170 members who attended out of the present membership of 450 included several from abroad. The annual report showed that the activities of the Group had been well maintained during the year, the highlight being the fourth International Symposium on Gas Chromatography which was organized in conjunction with the Gesellschaft Deutscher Chemiker, at Hamburg, in June 1962, and was attended by more than 700 people from 25 countries. The *Proceedings* of the Symposium was published in February and the editor, Dr. van Sway, is to be congratulated for completing the task so quickly.

The relationship of the Group with the Institute of Petroleum has been a fairly loose affiliation up to this year, but from October 1, 1962, the Institute agreed to carry out the major part of the routine administration, and to take over the printing and distribution of *Gas Chromatography Abstracts* and the *Proceedings* of the International Symposia which are held by the Group. This generous offer will lighten the burden on the Group's officers, committee members and abstractors.

The financial situation of the Group is sound and no increase in the fee for publications is contemplated at present. The abstracting service continues to be one of the most useful activities of the Group, and the next volume, *Gas Chromatography Abstracts, 1962*, will be published at an early date and will be the fifth volume of the series. After the re-election of the three retiring members of the Committee, Dr. A. T. James, Prof. A. I. M. Keulemans and Dr. C. J. Hardy, a brief statement of the future programme was given. The next informal symposium will be held in Exeter on September 27, and preliminary information has been given of the fifth International Symposium on Gas Chromatography, to be held at Brighton during September 8-10, 1964. Now that the technique of gas chromatography is no longer expanding so rapidly, it has been decided to change the format of the latter Symposium in order to have a more concentrated attack on the fundamental aspects of the separation process. The three morning sessions will be entirely devoted to this theme, with invited papers given by recognized authorities, followed by about three submitted papers in each session. The afternoon sessions will be devoted to informal discussions on various subjects such as essential oils, process monitoring and control, separation of permanent gases, with critical summaries only being published in the final proceedings.

The informal symposium opened with Mr. C. S. G. Phillips in the chair and a short speech of welcome was given by Dr. J. F. J. Dippy, head of the Chemistry Department and vice-principal of the Chelsea College of Science and Technology. The local arrangements were made by Dr. W. A. Ross of the Chemistry Department.

Dr. M. J. E. Golay (United States), who is well known for his work on capillary columns, gave the first paper by invitation on "Some Implications of Recirculated Gas Chromatographic Columns". Dr. Golay drew an analogy between gas chromatography and spectroscopy by comparing single-pass columns and recirculated columns with, respectively, gratings, which give a complete spectrum, and interferometers, which give details of a small part of a spectrum. The advantages and disadvantages of gas chromatography and distillation for dealing with

samples ranging in size from 10^{-7} to 10^{11} g were then discussed in terms of Table 1.

Table 1

Sample size (g)	Suitable gas chromatographic column	Scale of distillation
10^{-7}	Capillary	
10^{-4}	Small packed	
10^0	Preparative	Small batch
10^3	Re-circulated	Medium batch
10^6		Large batch
10^9		Continuous (with column increasing in size to 'giant')
10^4 - 10^{11}		

With a sample size of 10^{-7} g the purpose of a capillary column is to give a detailed analysis of a complex mixture just as a spectrometer analyses a spectrum. There is no comparable distillation technique; in fact, Dr. Golay seriously suggested that it was not feasible that ultra-micro distillation columns could be made for various reasons, even by intelligent ants. In the sub-mg range 'time is the essence' and gas chromatography is favoured because the height equivalent of a theoretical plate is in the sub-mm range, whereas it is of the order of a few cm for a distillation column in a gravitational field. In the region of 10^{-4} - 10^0 g the 'hold-up' volume which must be present in a distillation column is an important disadvantage, because there is no such 'hold-up' in a gas chromatographic column and all the desired material can be recovered with an efficient collection system. In going from the g to the kg scale, 'hold-up' is not so important, but the cost of a conventional gas chromatographic column increases approximately with the size, whereas the cost of a distillation column does not increase so much with size. Dr. Golay predicted that it is in this region that recirculated gas chromatography would compete increasingly with distillation and with conventional gas chromatography. It is important to note that the resolution of a recirculated column is proportional to n , the number of plates, and not to n^2 , as in conventional single-pass gas chromatographic columns. When the sample size exceeds 10^3 g the initial cost and the cost of operation become more important. With gas chromatographic columns the cost of the packing material would be high, and the use of even clean nitrogen for the carrier gas would become too expensive, while the cost of using helium would be prohibitive. The cost of cleaning the packing of a column would far exceed that of cleaning a distillation column. Hence distillation is seen to be pre-eminent in this region, and a modern giant distillation column at an oil refinery could not be replaced by a giant gas chromatographic packed column. The paper stimulated much general discussion which had to be curtailed by the chairman to avoid lunch being missed.

The afternoon session was opened by Dr. R. P. W. Scott with a short prepared contribution on "The Heavy-loading of Analytical Scale Columns", which was extra to the scheduled programme. Although it has been known for some time (Pollard and Hardy, *Chem. Indust.*, 527 (1956); on the preparation of pure formic acid and pure ethyl nitrate) that simple mixtures could usefully be separated on analytical scale columns (3-5 mm diameter) at the 200-mg level, Dr. Scott introduced a new idea of 'heavy-loading', as he wishes to call the method, for the separation of 200 mg and larger samples of multi-component mixtures. The method is partly an extension of the idea of Daniels and Richmond (*Chem. Indust.*, 1441; 1961) of putting a sample on a column and waiting a short time before commencing elution with the carrier gas. When a large sample is normally added to a small column

serious overloading occurs and steep fronts and trailing rears to the peaks are obtained. However, Dr. Scott has shown that symmetrical peaks can be maintained by allowing a period of time with no flow, and then increasing the flow rate exponentially with time. For example, a seven-component mixture of 0.175 ml. total volume was well separated by leaving it for 5 min on top of a 4.5 ft. (1,600 plate) column of 3–4 mm diameter containing 25 per cent squalane on 100–120 mesh brick dust at 50° C, and then increasing the flow rate from 0 to 600 ml./min over 75 min; an argon detector was used. Dr. Scott suggested that a 1 ml. sample of this complexity could be separated readily on a 1-cm diameter column and that the method should be of great help for preparative separations on analytical columns. Unfortunately, however, no details of the exponential flow controller were released.

Mr. P. L. Timms presented a paper with Mr. C. S. G. Phillips on "The Study of Silicon and Germanium Hydrides by Gas Chromatography", in which the preparation, separation and characterization of a large number of silicon, germanium, and mixed silicon-germanium hydrides was discussed. The last-named new class of compounds are of particular interest because they have: (1) analogues in the pure silicon and germanium hydrides; (2) position isomers with different relative positions of the germanium and silicon atoms; (3) structural isomers similar to the normal- and iso-compounds containing carbon and hydrogen. These isomers were exemplified by iso-Si₃Ge₂H₁₂ with the chain structure Si—Si(Ge)—Si—Ge; its analogue (1) is Si—Si(Si)—Si—Si, a position isomer (2) is Ge—Si(Ge)—Si—Si and a structural isomer (3) is the normal compound Si—Si—Si—Ge—Ge. With five atoms in the chain there are a total of 54 possible isomers.

The mixed hydrides are produced by the reaction of an alloy of magnesium, silicon, and germanium with mineral acid. They are spontaneously inflammable, a fact which Mr. Timms well demonstrated by dropping a sample into a trough of water whereon there was a bright flash and a miniature atomic mushroom cloud of smoke, accompanied by much applause. These hydrides are therefore handled in a closed apparatus on a µg-mg scale and chromatographed with hydrogen or nitrogen as the carrier-gas and detected with a katharometer. The use of two columns, silicone 702 at 66° and tritolyphosphate at 20°, enables a large number of these isomers to be separated.

A variety of other techniques are combined with gas chromatography to characterize the compounds. The silicon to germanium ratio is determined by reaction of an unknown hydride with gold chloride to give a mixture of silicon tetrachloride, germanium tetrachloride and hydrochloric acid, which is separated on a gas chromatographic column and quantitatively determined in a gas density detector. The molecular weight can be determined to 1–2 per cent on a 50–100 µg sample by a pressure-volume measurement combined with a measurement in the gas-density balance. Branched chain hydrides can be distinguished from straight chain hydrides on a 5 Å molecular sieve column which absorbs the straight chain compounds. Pyrolysis is also useful because the products differ according to the structure of the parent compound, for example, *n*-Si₂Ge₂H₁₀ gives mainly Si₂GeH₈ and Si₂H₆, whereas *n*-Si₃GeH₁₀ gives SiGe₂H₈ and SiGeH₆, all of which can be separated by gas chromatography.

One of the most useful and illuminating pieces of work was a plot of the logarithm of the specific retention volume, V_g (ml. carrier gas per g stationary solvent), versus the chain length on silicone 702 at 64° C. All the *n*-germanes lie on one straight line which intersects the log V_g axis at zero chain length (this point is called the hydrogen point). All the *n*-silanes lie on a straight line which intersects the axis at the same hydrogen point. The iso-germanes and iso-silanes lie on straight lines which are slightly lower than the respective *n*-lines. From this plot it is possible to calculate the log V_g value for any mixed

hydride in terms of two constants and a sliding 'constant'. The first constant, $k_1 = 0.575$, is the log V_g increment per silicon atom, the second, $k_2 = 0.821$, is the log V_g increment per germanium atom. The third 'constant', $k_3 = 0.130 + 0.025 N_{Ge}/(N_{Ge} + N_{Si})$, depends on the number of Ge atoms (N_{Ge}) and silicon atoms (N_{Si}) in the chain, and represents the difference between *n*- and iso-compounds. It varies between 0.155 for $N_{Si} = 0$ to 0.130 for $N_{Ge} = 0$. A typical example is the hydride SiGe₂H₈ for which the calculated log $V_g = k_1 + 2k_2 = 2.22$ whereas the observed log $V_g = 2.20$.

The evidence so far obtained indicates that it is not possible to separate position isomers. The synthesis of, for example, Si—Si(Si)—Si—Ge, and Si—Si(Ge)—Si—Si, has been achieved but only one normal-width peak is obtained when they are gas chromatographed together and there appears to be no detectable difference in their retention volumes. The general conclusion on this work is that it represents a major step forward in the study of the non-metal hydrides. In the ensuing discussion two interesting points were raised, first, Dr. J. Smith pointed out that log V_g values of position isomers of long-chain ketones were almost identical, and Dr. Littlewood observed that the hydrogen point for these hydrides was not the same as that for hydrocarbons, and that the value for the latter was negative and about 0.1 ml. No immediate explanation of this point, which must be connected with the basic structure of these compounds, was forthcoming, but it obviously warrants further theoretical study.

Mr. J. V. Mortimer presented a paper with Mr. P. L. Gent on "The Use of Organo-clays as Stationary Phases" and pointed out the need for a stable and selective liquid phase for the separation of the C₈-aromatics and the isomeric xylenes. The liquid phase most commonly used for the separation of these substances is 7,8-benzoquinoline, which is appreciably volatile at 70°–100°, and will not give reproducible results or permit automatic operation without difficulty; below 50° it is a solid and gives poor separation. A type of montmorillonite or aluminium silicate matrix, known as 'Bentone' (which was used for gas chromatography by White and Cowan in 1957), has therefore been re-examined and combined with conventional liquid phases with success. 'Bentone 34', a dimethyldioctadecyl substituted clay, has given good results on its own but only with small samples (0.02 µl.) and sensitive detectors (ionization type); however, equal parts of 'Bentone' and a silicone oil together with ten parts of 'Celite' packed into a 12-ft. column and operated at 70° with a flow rate of 120 ml./min and a conventional thermistor detector gave well-resolved symmetrical peaks for a 3 µl. sample of *para*-, *meta*-, and *ortho*-xylene (in that order of elution) and a complete separation of the C₈-aromatics in 40 min.

The separation of the aromatic and naphthenic hydrocarbons can be altered appreciably by varying the temperature and the ratio of the amount of silicone oil to the amount of 'Bentone'. Various grades of silicone oil, and also squalane, apiezon grease and polyethyleneglycols, can be used to modify the properties of the 'Bentone', and examples of other separations were also given, the *p*-, *m*-, and *o*-dichlorobenzenes and *p*-, *m*- and *o*-cresols.

"Modifications of Solid Supports for the Gas Liquid Chromatographic Measurement of the Characteristics of Solid Supports" were then discussed by Dr. J. F. K. Huber in a paper with Prof. A. I. M. Keulemans. The ideal properties of a support are a uniform surface structure, a low surface area, weak adsorption for all solutes, good mechanical strength, and low cost. Dr. Huber showed that the 'Sterchamol' support now widely used can be greatly improved by heating it for 100 h at 1,150° C. This treatment reduces the specific surface from 3.4 to 0.09 m²/g, but scarcely changes the specific volume, 0.44–0.42 cm³/g. The specific volume of pores of 75–75,000 Å diameter (mercury method) is reduced from 0.5 to 0.11 cm³/g and those > 75,000 Å from 0.85 to 0.36 cm³/g. The

adsorption of methanol was very considerably reduced on heated 'Sterchamol' compared with normal 'Sterchamol'. Another widely used support, 'Chromosorb W', was found to be significantly better than 'Sterchamol', but not so good as heated 'Sterchamol'. The practical improvement resulting from this treatment was demonstrated in the symmetrical peaks obtained for C_3 - C_6 ketones, alkyl-acetates, and up to C_6 alcohols on a 1 m $\times$ 4 mm diameter column of 1 per cent squalane on heated 'Sterchamol' at 80° C. In the discussion which followed, Dr. Huber said that he used a small mesh size (about 100 B.S.S.), that heating in air, nitrogen or vacuum produced the same effect, and that he only sieved out fine particles before use, and did not regrid after heating in order not to expose fresh surfaces which might have high adsorptive capacity. It is possible to absorb up to 10 per cent of a liquid phase on the heated 'Sterchamol' if required.

The final paper of the meeting was on "The Effect of Stationary Phase Viscosity on Column Efficiency", by Mr. S. J. Hawkes. References in the literature to this effect are few and contradictory and therefore Mr. Hawkes has attempted to correlate data on a variety of liquid phases over a range of temperature, and to suggest the minimum temperature at which well-known liquid phases can be used for a given resolution. The relationship between the diffusivity, D , in the liquid phase and the viscosity, η , was discussed in terms of the Arnold equation, which proposes that $D \propto \eta^{-2}$, and the Herzog equation, which proposes that $D \propto \eta^{-1}$. The results of Littlewood for *n*-octane and 2-methyl-pentane on tricesylphosphate supported on glass beads were taken to show that a twelve-fold change in viscosity (with temperature) only gave a 1.5-fold change in the diffusivity term if this were assumed to be proportional to η^{-1} , compared with a 6-fold change if assumed proportional to η^{-2} . Similarly, benzene on polypropylenesebacate supported on treated 'Celite' over the range 25°-145° C gave an almost constant η^{-1} term.

Mr. Hawkes therefore considered that the Herzog equation best fitted the data, but that an additional empirical factor was necessary to make the diffusivity factor constant for all solutes on a given liquid phase. The experimental values for the height equivalent of a theoretical plate agreed with the values calculated from the modified Herzog treatment within a factor of 3 for various liquid phases, temperatures, and solutes. One conclusion was that there should be little restriction on the minimum operating temperature of packed columns except perhaps for solutes with low partition coefficients or for complex liquid phases, for example, substituted adipates and sebacates. However, with capillary columns the effect of viscosity can be important if the thickness of the liquid film is 10^{-4} cm, but with a film thickness of 10^{-5} cm there should not be serious difficulties.

This paper stimulated considerable discussion, and Dr. R. P. W. Scott stressed the practical importance of the effect of temperature on the resolution of a pair of solutes in a column rather than its effect on the maximum efficiency. It was pointed out by Dr. A. J. P. Martin that good separations can be achieved with a stationary phase of rubber, which has an extremely high viscosity. Dr. T. Smith commented that silicone gums with a high viscosity also give good separations in practice, and that he considered that the relative polarities of solutes and solvents was of importance in determining the effect of viscosity. He expected the behaviour of non-polar solutes to be little affected by the viscosity of a non-polar solvent but the interaction of polar and non-polar molecules to be considerably affected by viscosity.

In conclusion, it would seem that this symposium was successful because it offered something for everyone rather than specializing on one narrow topic, and that the Group should be encouraged to give similar balanced programmes at future meetings.

C. J. HARDY

MICROBIOLOGY AND WORLD FOOD SUPPLIES

AT the eighth International Congress for Microbiology, held in Montreal during August 1962, the following resolution was adopted:

(1) The International Association of Microbiological Societies, in sympathy with the Food and Agriculture Organization's Freedom from Hunger Campaign, has noted with concern the widening gap between the global rates of increase of population and of food supply, at a time when there already exists famine or near-famine in many parts of the world. The Association has accordingly considered how microbiology might help towards a future need, clearly indicated, to increase world food production by all conceivable means.

(2) One attack on this problem is to improve the fertility of soils, in which connexion the following would be helpful: (a) A study of thermophilic and mesophilic micro-organisms capable of more rapidly transforming such non-food wastes as sawdust, straw, weeds, leaves, sludge, etc., into suitable organic matter of manurial value. (b) Research on the effect of herbicides, fungicides and other chemicals on micro-organisms, in order to attempt to control soil populations. (c) Further studies on the effectiveness and wider distribution of *Azotobacter*, *Rhizobium* and other micro-organisms capable of fixing atmospheric nitrogen.

(3) There is also the possibility of producing, from appropriate micro-organisms, agriculturally useful substances, such as plant growth factors and inhibitors.

(4) Another obvious line of attack is to prevent spoilage of food by micro-organisms. There are well-proved ways of doing this, such as drying, salting, refrigeration or canning; and there are new methods of promise, such as

the use of antibiotics or irradiation; all these are worth investigating. On an international view, however, it is much more urgent to apply what is already known to countries where such methods are under-developed, rather than to devote effort to minor improvements in existing procedures. Moreover, it must be recognized that even if food spoilage by microbes were entirely prevented, the increase in total available food would be small (of the order only of a few per cent, though the benefits might be greater in some places).

(5) To change the situation radically, sources of food additional to orthodox agricultural production must be sought for man and his domestic animals. It should be realized that micro-organisms should be capable of supplying some of these; for micro-organisms are able to produce edible protein, fat or carbohydrate, and vitamins, from materials entirely inaccessible to human or mammalian digestion, yet do not require agriculturally useful land.

(6) As examples of micro-organisms worthy of examination, the following are suggested: (a) Organisms utilizing existing agricultural or industrial by-products (food yeast is the best known example). (b) Fungi and bacteria decomposing cellulose or hemicellulose (for example, woody plant tissue). (c) Fungi attacking wood, especially lignin (some of these are known to be edible). (d) Organisms which decompose the larger sea weeds. (e) Organisms capable of multiplying in various effluents (for example, aquatic fungi). (f) Bacteria capable of oxidizing methane or other hydrocarbons. (g) Photosynthetic algae or bacteria (*Chlorella* is the best investigated example). Particular interest would attach to organisms capable