LETTERS TO THE EDITOR.

[The Editor does not hold himself responsible for opinions expressed by his correspondents. Neither can he undertake to return, or to correspond with the writers of, rejected manuscripts intended for this or any other part of NATURE. No notice is taken of anonymous communications.]

The Stresses in Masonry Dams.

IF Prof. E. Brown will refer again to my letter published in NATURE of January 2, he will see that I specifically stated that I did not question that in so far as the dam acted as a horizontal beam, the stresses $\widehat{xx}$ and $\widehat{zz}$ will be different in an actual dam and a slab dam. The real point is that Prof. Karl Pearson has said that, apart from any action of this kind, the stresses $\widehat{xx}$ and $\widehat{zz}$ in a slab dam and in an actual dam are widely different. Thus, on p. 11 of Pearson and Pollard's paper, he says Messrs. Wilson and Gore put the stress $\widehat{yy}$ zero, and "hence the vertical and horizontal pressures they calculated have no direct application to real dams." He has since explained in *Engineering*, September 20, 1907, that he did not here refer to any action of the kind mentioned by Prof. Brown and by myself in my original letter to you, but that, apart from any action of this kind, the stresses $\widehat{xx}$ and $\widehat{zz}$ are entirely different in a slab dam and a long dam. Messrs. Wilson and Gore deduced the stresses for their slab by the equations

$$\widehat{xx} = \frac{E}{\left(1 - \frac{1}{m^2}\right)} \left(e_1 + \frac{e_2}{m}\right)$$

$$\widehat{zz} = \frac{E}{\left(1 - \frac{1}{m^2}\right)} \left(e_2 + \frac{e_1}{m}\right),$$

where E is Young's modulus, e_1 and e_2 the measured strains, and m Poisson's ratio. So far as I can see, these equations give correctly the stresses $\widehat{xx}$ and $\widehat{zz}$ for the slab, and if my reasoning in my previous letter to you is correct, these stresses will be unaltered when the slab forms part of a complete dam and is then exposed to stresses $\widehat{yy}$ at right angles to the plane of the other two.

H. M. MARTIN.

83 St. James's Road, Croydon, January 10.

MAY I ask whether the interesting experiments on gelatin models of masonry dams, recorded in your issue for January 2, p. 209, do not ignore one factor on which the stability of actual dams is calculated largely to depend, namely, the weight of its materials?

This factor does not seem to be reproduced in the model, and I conceive that it may account for the rupture depicted on p. 210, which is hardly of a kind that one would expect to have to guard against in a real dam.

OLIVER LODGE.

MR. MARTIN in his letter to NATURE of January 2 cites the body stress-equations of elasticity

$$\left. \begin{aligned} \frac{axx}{dx} + \frac{dxx}{dz} &= 0 \\ \frac{dxx}{dx} + \frac{dzz}{dz} + pg &= 0 \end{aligned} \right\} \dots (i)$$

and appears entirely to overlook the fact that two equations will not suffice to determine the three stresses $\widehat{xx}$, $\widehat{zz}$, and $\widehat{xz}$. There is another relation between the stresses, and this relation depends on the relation between the strains, which is purely geometrical, namely,

$$\frac{d^2\sigma_{xz}}{dxdz} = \frac{d^2s_x}{dz^2} + \frac{d^2s_z}{dx^2} \dots (ii)$$

In substituting for these strains in terms of the stresses the resulting third equation differs for the cases of the dam and of the slab.

NO. 1095, VOL. 77]

For the case of the dam abutting at its terminals against rigid supports:—

$$4 \frac{d^2\widehat{xz}}{dxdz} = 2\eta \left(\frac{d^2}{dx^2} + \frac{d^2}{dz^2} \right) (\widehat{xx} + \widehat{zz}) + \left(\frac{d^2}{dz^2} - \frac{d^2}{dx^2} \right) (\widehat{xx} - \widehat{zz}) \quad (iii)$$

For the slab with free faces:—

$$4 \frac{d^2\widehat{xz}}{dxdz} = \frac{1+2\eta}{3-2\eta} \left(\frac{d^2}{dx^2} + \frac{d^2}{dz^2} \right) (\widehat{xx} + \widehat{zz}) + \left(\frac{d^2}{dz^2} - \frac{d^2}{dx^2} \right) (\widehat{xx} - \widehat{zz}) \quad (iv)$$

where η is Poisson's ratio.

Messrs. Wilson and Gore have determined their $\widehat{xx}$, $\widehat{zz}$, and $\widehat{xz}$ from measuring σ_{xz} , s_x , and s_z on an india-rubber slab with, I presume, $\eta = \frac{1}{2}$. Their values for these stresses therefore ought to satisfy (i) and (iv); it is difficult to understand how Mr. Martin can believe them to satisfy (i) and (iii) with $\eta = \frac{1}{2}$, which is needful in the case of the masonry dam.

To Sir Oliver Lodge I can only reply:—"Read our memoir and you will find that the influence of the weight of the dam is fully discussed, and experimentally determined. You will also find that the actual tearing was only reached by 'excessive water pressure.'"

With regard to Prof. Brown's views on the effect of the terminals, the following words are used to limit the actual theory applied:—"Let us suppose an indefinitely long dam, or if it be of finite length that its terminals abut against rigid supports." The words *abut against* were purposely used instead of *are built-in* to mark what conditions were being assumed. It is quite another point how far my theoretical dam may be considered an approximation to a real dam. Prof. Brown, emphasising the variability of conditions in any practical case, says that engineers "have used a simple but approximate method of estimating stresses in a dam, based on the flexure of beams." My criticism is that this is not an approximation at all, and that if it were they have neglected to apply their own conditions to the vertical sections, in which case they would have found any existing dam so lacking in stability that they would have promptly dropped a theory which, if carried to its logical conclusion, condemns all existing dams! Now, when an engineer treats a dam as a beam, he forgets two points:—(1) That the length of a beam must be large compared to the linear dimensions of the cross-section. In the case of the dam, its base, the built-in cross-section, is of the same dimension as to depth as the length of the beam, i.e. the height of the dam. The ordinary formulæ of flexure are thus absolutely inapplicable, as anyone who knows de Saint-Venant's classical memoir on flexure will at once realise. (2) That the faces of the beam must be free to expand in order that the theory may apply. In applying his theory of flexure, therefore, the engineer, so far from building-in his terminals, does not even suppose them to abut! I contend that if Prof. Brown's balcony were 100 feet broad, but half a mile or a mile long, he would find little difference in the stresses except relatively close to the abutments, whether he supposed the terminals abutted or were built-in. In any case, I am convinced on both theoretical and experimental grounds that for the bulk of the dam far better results will be obtained by applying the uniplanar equations of stress than by any attempt to deal with a solid practically as broad as it is long by a theory of flexure.

That the terminal conditions produce effects goes without saying; I agree with Prof. Brown that we should, if possible, consider them, but their order of importance is that of two terminal supports to a balcony, say 1 foot broad, 1 foot deep at the built-in edge, uniformly loaded, and perhaps 50 feet long. Such effects are purely secondary, and it will be time enough to consider them when we have reached some agreement as to the main stresses; these stresses can be fairly reached by taking, as I have done, an indefinitely long straight dam *abutting* against rigid terminals.

With most of Prof. Brown's statements in his appreciative criticism I am in complete harmony. No theory will replace local knowledge—that of the geologist as well as that of the engineer—no theory will perhaps be of equal value with past experience, but it can be helpful and even