The Gas Industry.

THE extent to which the gas industry is trustee for the efficient utilisation of the nation's coal resources will be realised when it is remembered that one of the London gas companies, with a production representing about 15 per cent of the total output of towns' gas in Great Britain, distributes annually approximately as much energy as the whole of the electrical undertakings in the country. The industry has reason to be proud of its stewardship, for the thermal efficiency of the process of carbonisation of coal as practised day in, day out, is from 70 to 80 per cent. Thermal losses are inevitable in any actual thermal process, and the operations of the gas industry are not outside the ambit of the second law of thermodynamics, high though the efficiency of the carbonising process may be. Increasing attention has in recent years been paid to potential sources of loss of thermal energy in gas-making processes in general, and the results of investigations, more especially concerned with methods of manufacture of water-gas, are embodied in some of the Reports issued by the Joint Gas Investigation Committee of the Institution of Gas Engineers and the University of Leeds, and by the Fuel Research Board.

"Gather up the fragments that remain, that nothing be lost." In the sixth Report of the Gas Investigation Committee (*NATURE*, August 11, 1923, p. 222) it was shown that the efficiency of production of blue water-gas as ordinarily practised in a plant without waste heat boiler is 46 per cent. The seventh Report showed that by the use of a waste heat boiler, this thermal efficiency could be increased to 53 per cent. In the tenth Report, details are given of large scale experiments carried out to ascertain whether by reducing the depth of fuel bed, as in the Dellwik-Fleischer process, the efficiency of manufacture of blue water-gas might be still further increased. During the "blow" period of operation of the plant, a regulated air blast is admitted to the fuel bed, resulting in the production of a mixture of carbon dioxide and carbon monoxide. The thermochemical equations show that during this period more than three times as much heat is liberated when the product is wholly carbon dioxide as when only carbon monoxide is produced. During the air-blow, therefore, it would appear to be desirable to obtain the maximum production of carbon dioxide. Carbon dioxide reacting with carbon yields carbon monoxide. During the "run" period, steam is passed over the incandescent fuel bed, and a mixture consisting principally of hydrogen, carbon monoxide, and carbon dioxide is produced. A consideration of the reactions occurring indicates that factors, referring to the temperature and depth of the fuel bed, operative during the two periods, influence the efficiency of the process as a whole in opposite directions. The results incorporated in the tenth Report show that the manufacture of blue water-gas by the intermittent process described can be carried out more efficiently and with a greater output per day when the carbon dioxide-carbon monoxide ratio in the blow gas is about 0.9, than when this ratio is greater than unity, and that operating in this manner, the efficiencies reported in the sixth Report might be raised to as high as 60.4 per cent.

Clause 5 of the Gas Regulation Act (1920) prescribes that, in the case of certain gas undertakings, the prescribed apparatus for testing the gas in order to safeguard the consumers' interests "shall include a calorimeter for the production of a continuous

record of the calorific value of the gas." Considerable ingenuity has been shown in the construction of instruments for the specified purpose. These have embodied essentially different principles. The devices incorporated in the Simmance instrument are intended to control the flow of the heating fluid (gas) and the heated fluid (water) at respective constant rates independent of changes of temperature and pressure. In the Fairweather recording gas calorimeter, the rate of supply of gas is uncontrolled so far as temperature and pressure changes are concerned, and an ingenious device regulates the supply of water to the calorimeter in proportion to the varying supply of gas. In Prof. Boys's instrument, both gas and water are doled out positively at predetermined fixed and unalterable rates. In the calorimeter due to C. C. Thomas, air is employed as calorimetric fluid and its rate of supply to the instrument is readily maintained in strict relation to the supply of heating fluid, by means of coaxial meters having appropriate relative sizes. The Beazley calorimeter is of the "method of mixture" type.

In the eighth Report of the Gas Investigation Committee, details are given of exhaustive and searching tests to which the Fairweather recorder has been submitted, with the view of ascertaining its suitability for application in accordance with the requirements of the Act. It will be readily understood that as the accepted recorder or recorders will, in certain eventualities, be employed as the arbiter determining the fulfilment or otherwise by gas undertakings of their statutory obligations, considerable caution is necessary in the acceptance by the gas industry of any recording calorimeter as entirely trustworthy. The Report referred to indicates that the Fairweather recording calorimeter, operated under favourable conditions as to constancy of density of the gas supplied, the temperature and quality of the water supply, and receiving occasional skilled attention, should afford a record correct to within 0.5 per cent. The accuracy is decreased under variable conditions, and suggestions of constructional alterations are made in the Report whereby the instrument may be improved in this respect. The gas industry waits upon the advent of Prof. Boys's ingenious recorder in the sure hope that it will be relieved of considerable anxiety and expense in the matter of statutory testing of the calorific power of towns' gas.

The ninth Report of the Committee is devoted to the subject of aeration in gas-burners, a factor upon which the efficient operation of all atmospheric gas-burners depends, but upon which—although the Bunsen burner dates from 1855—very little trustworthy information has been hitherto available. The Report is a preliminary account of an experimental investigation of the influence of a variety of factors—the length, diameter, and outlet resistance of the burner tube, the rate, pressure, and specific gravity of the gas, the size and type of injecting jet, etc.—upon the aeration of the jet of gas.

The War period was characterised by the formation of Research Associations within certain industries. The outbreak of war was not necessary to impress upon the gas industry the prime necessity of research. Long before that its Gas Investigation Committee functioned, and the present Reports indicate that the Committee is alive to its duties and responsibilities both to the industry and the gas-using public.

J. S. G. THOMAS.