used or wishes to use, in terms that are universally accepted, so that his colleague in another continent will know immediately the nutritional requirements, the state of freedom from specific infection, the pedigree and the possible sources of the same strain.

The quality of the animals sooner or later limits all work for which they are used. Cancer workers were among the first to realize this, and much of their research would to-day be impossible without the highly defined strains of mouse and rat being used. In the field of bio-assay the amount of frustrated effort resulting from the use of inadequate animals can only be estimated by the minority who have taught themselves, if not their colleagues, the value of good ones. But it is of little benefit to swell the minority into a majority unless, first, there is agreement on the definition of quality and, second, the better animals can be produced in sufficient numbers. The first of these provisos is a matter for the International Committee. Those who hold the purse strings of research can facilitate the second by taking the laboratory animal from the bottom of the list of claims and placing it somewhere near the top. Lastly, the research worker himself can give decisive support by insisting on being provided with better animals, and making good use of them when he gets them.

W. LANE-PETTER

¹ See *Brit. Vet. J.*, **111**, 282 (1955).

² See *Nature*, **175**, 26 (1955).

GAS CHROMATOGRAPHY

A SYMPOSIUM on gas chromatography, organized by the Hydrocarbon Research Group of the Institute of Petroleum, was held in London during May 30–June 1. The meeting was attended by nearly four hundred members from thirteen different countries, and the thirty-four papers presented covered all aspects of gas chromatography. The full proceedings, complete with discussion, will be published by Messrs. Butterworths shortly. It was felt that in this rapidly growing field, nomenclature and methods of presentation of data should be standardized as early as possible. A special Committee was accordingly nominated, comprising Dr. A. J. P. Martin (chairman), Mr. C. S. G. Phillips (secretary), Mr. D. H. Desty, Dr. E. Glueckauf, Dr. A. T. James and Dr. A. I. M. Keulemans. At the end of the symposium the chairman presented the Committee's recommendations, which were as follows.

Nomenclature

(a) That the term 'gas chromatography' be used to describe all chromatographic methods in which the moving phase is a gas, and that the term 'vapour phase chromatography' be no longer employed.

(b) That the term 'gas-liquid chromatography' be used to describe all gas chromatographic methods in which the fixed phase is a liquid (distributed on an inert support).

(c) That the term 'gas-solid chromatography' be used to describe all gas chromatographic methods in which the fixed phase is a solid (for example, charcoal, zeolites).

(In this report the Committee uses the term 'chromatography' only where a fixed phase is involved.)

Presentation of Retention Values in Gas-Liquid Chromatography

Since for many purposes it is unnecessary to determine absolute retention volumes, and since, by the use of an internal standard the corrected retention volume per gram of liquid phase of which has been measured, all values can be compared, it is recommended:

(a) That the retention values (retention volumes or retention times of concentration maxima) should be expressed relative to an internal standard; that in presenting values for a series of substances, the internal standard substance should be chosen so as to have a retention value near the middle of the series; that internal standards with very low retention values should not be used; that retention values should be corrected for dead-volume (by injection of a permanent gas) before these values are expressed relative to the internal standard; that such results should be quoted with the exact composition of the fixed liquid phase, the nature of the support material, and the exact temperature at which the column has been operated; that column temperatures be controlled by means of vapour jackets or circulating-fluid (liquid or air) jackets. It is felt that results obtained with a column which varies in temperature (along its length, or during the course of a run) will be of little value.

(b) That whenever possible the corrected retention volumes per gram of liquid phase (that is, V_g values) should be measured for the internal standard, careful corrections being made for the pressure drop across the column. These values may be obtained by the following procedure:

(1) Determine the volume of gas (measured at the exit pressure of the column, and corrected to dry gas at the column temperature) which has passed from the column between the emergence of the dead-volume (permanent gas) peak maximum and the peak (concentration) maximum of the internal standard.

(2) Correct this volume for the pressure drop across the column by multiplying it by the reducing factor

$$\frac{3}{2} \cdot \frac{(p_1/p_0)^2 - 1}{(p_1/p_0)^3 - 1}$$

where p_1 is the pressure at the beginning of the column, and p_0 the pressure at the exit. The values of p_1 and p_0 should be recorded.

(3) Divide the corrected retention volume so obtained by the weight (in grams) of the fixed liquid phase.

The Committee has envisaged the possibility that the measurements in sections (a) and (b) may sometimes be made by different workers. Attention is directed to the need, in connexion with the corrected retention volume, of accurate measurements of flow rate. It is not considered that rotameter readings are of sufficient accuracy for this purpose, and the use of soap-bubble or capillary flowmeters is suggested.

(c) That the following substances should be used as internal standards: *n*-butane; *iso*-octane (2:2:4-trimethylpentane); benzene; *paraxylene*; naphthalene; methylethyl ketone; *cyclohexanone*; *cyclohexanol*.

(d) That in presenting retention values for new substances, one or more of the following liquid phases

should be used (temperature ranges (°C.) in parentheses): *n*-hexadecane (20 to 50); squalane (20 to 150); benzylidiphenyl (80 to 150); dinonyl phthalate (20 to 100); dimethylformamide (-20 to 20); diglycerol (20 to 100).

(It is hoped that these liquids will be made available in standard purity.)

That while it will be of great value if studies are made on the effects of varying the support material and the packing ratio, a mixture of 20 parts by weight of fixed liquid to 80 parts by weight of inert support (preferably 'Celite 545') be used as a standard.

(e) That with skew peaks the results for retention values should be extrapolated to zero sample size.

In drawing up these recommendations the Committee has in mind low-temperature (up to 150° C.) columns. It is felt that the subject of high-temperature (operated at above 150° C.) columns is not sufficiently developed to put forward rigid proposals.

Column Resolution

That column resolution be expressed in terms of theoretical plate numbers; that a theoretical plate number should always refer to a particular substance, and that the theoretical plate number of the internal standard should always be given. It is recommended that theoretical plate number should be determined by the following procedure: tangents (see Fig 1) are

Fig. 1

drawn to the peak at the points of inflexion. The lengths of base line (y) cut out by these two tangents is then measured. The length from the start of the run (that is, including dead-volume) to the middle of this base-line section (x) is also measured. Then number of theoretical plates = $16 (x/y)^2$.

Vapour Detectors

In view of the often widely different performance characteristics of the detectors now used in gas chromatography, the Committee does not feel that it would be desirable at this stage to lay down any definite rulings on the manner in which detector sensitivities should be expressed. However, it wishes to emphasize that in describing detector performance attention should be paid to the following:

(a) The sensitivity should be expressed in terms of vapour concentrations rather than sample size. Details should always be given of the stability (under normal rather than favourable working conditions) of the base line, both for short periods (noise) and for long periods (drift). The sources of these instabilities should be indicated wherever possible (thus the effects of vibration may be more serious under some working conditions than under others).

(b) Linearity of response.

(c) Necessity for calibration.

(d) Response time and volume of detector.

(e) Reproducibility.

(f) Temperature-range of operation.

(g) Range of vapours, stressing types of vapour for which the detector is particularly suited or unsuited.

It is intended to form a discussion group for gas chromatography under the auspices of the Hydrocarbon Research Group in the near future, which will be responsible for holding further meetings as required and also for implementing the above recommendations, particularly as regards the collection, assessment and distribution of retention volume data.

D. H. DESTY

CENTRAL ELECTRICITY AUTHORITY

REPORT FOR 1955-56

THE eighth annual report and statement of accounts of the Central Electricity Authority, which covers the year ended March 31, 1956*, is of particular interest for its reference to the contribution of nuclear power plant. At March 31, 1956, the Authority owned 274 power stations, with a total installed generating capacity of more than 20.6 million kW., there being a net increase in maximum output capacity of about 1.5 million kW. during the year, and a further increase of 45 per cent is planned during 1956-61. The 1961 programme of plant approved during the year is for 2,379,000 kW., of which 250,000 kW. is of nuclear plant, and consent was given in July 1956 to the establishment of such stations at Berkeley, Gloucestershire, and Bradwell-on-Sea, Essex. Competitive designs for these first two stations, of a capacity of not less than 150,000 kW., are being prepared by each of four industrial groups, and the greater part of the cost of electricity from such stations is expected to arise from capital charges. Stress is laid in the report on the severity of the requirements for siting such stations, twelve of which are included in the Authority's programme for the next ten years. Arrangements have also been made for the supply of heavy fuel oil to seventeen power stations, and it is estimated that the total consumption of oil will rise to more than 5.5 million tons a year, equivalent to some 9 million tons of coal, while one of two hydro-electric projects to receive Parliamentary sanction is a 300,000-kW. pumped storage scheme in North Wales, the first of its kind in Great Britain. With the introduction of nuclear power plant on a large scale for base-load operation, other new plant must be flexible in operation and suitable for two-shift workings and daily starting-up and shutting-down as required, and new 200,000- and 120,000-kW. reheat units are being designed accordingly. The Authority continues to be the largest individual user of coal in Great Britain and in 1955-56 consumed 41.04 million tons of fuel (39.87 million tons of coal), or 6.6 per cent more than in the previous year, with a 9.4 per cent increase in the electricity generated.

The main research laboratories of the Authority are at Leatherhead, and are occupied mainly with problems relating to the design and operation of power stations, including the efficient combustion of coal, the causes of boiler fouling and corrosion and methods of alleviation, particularly the fouling effects of certain coal constituents, the use of electronic equipment in studying operational problems, and, in co-operation with the Forest Products Research

* Central Electricity Authority. Eighth Report and Statement of Accounts for the Year ended 31st March, 1956. Pp. viii+244+8 plates. (London: H.M.S.O., 1956.) 10s. 6d. net.