The Symposium received support from U.S. Army Ballistic Research Laboratories, National Aeronautics and Space Administration, National Science Foundation, National Academy of Sciences—National Research Council Committee on Fire Research, the British Section of the

Combustion Institute, and from many industrial firms in Britain, the United States and Canada.

The next symposium will be held in 1966 at Berkeley, California.

E. M. BULEWICZ

THERMAL CONDUCTIVITY

THE expanding field of new materials and their use in all branches of technology, particularly those involving transfer of heat, has increased the scope of work on thermal conductivity during the past two decades and created a revival of interest in the subject. The problems are international, and this was apparent during July 15–17 when 150 invited delegates, representing 11 countries, met at the National Physical Laboratory to discuss their work in this subject. For many years the Laboratory has been involved in work on the thermal properties of materials and it was, therefore, a most appropriate venue for such a gathering.

The comprehensive programme of 50 papers contained a majority which were devoted to methods of measurement, supplemented by others which included results for some particularly important materials in solid, liquid or gaseous state. In some of the cases where metals or semiconductors were reported on, the results were accompanied by an analysis which was of value in relating the behaviour of real materials to the theory of solids.

Much attention was directed to the difficulties encountered in the measurement of thermal conductivity over the very wide range of temperature now considered of practical importance. It was also realized that poor experimental work cannot be explained with elaborate hypotheses; measurements to high accuracy are required before any attempt is made to assess materials or investigate theories. Significant advances have been made in methods for all conductivity ranges both for fundamental purposes and for the less accurate but rapid practical requirements.

Some particularly important developments have been made to the original unmatched guard apparatus first proposed by M. J. Laubitz (National Research Council, Ottawa). He has dispensed with the guard tube and now undertakes the measurement of temperature profile along the axis of his two-sectioned centrally heated rod by means of a tightly fitting thermocouple sliding inside an axial hole. These accurate measurements coupled with a reasonably simple mathematical analysis of the system seem capable of yielding results very quickly, since equilibrium conditions are attained rapidly, at temperatures up to 1,000° C. For basic studies of materials at these temperatures this is an important step forward and the possibilities of extending its temperature range by using optical pyrometry were seen immediately.

H. E. Robinson (U.S. National Bureau of Standards) discussed forms of line heat sources that could be used as heaters in apparatus for measurements at lower temperatures on insulating materials in disk and slab form. These new configurations lend themselves more readily to mathematical analysis, they are more simple to use and would appear to be able to yield more accurate results.

R. Berman (Clarendon Laboratory, Oxford), during a session devoted to low temperatures, described a significant new measurement technique whereby thermal conductivities can now be undertaken between 1° and 300° K using a single method involving thermocouples for temperature measurements. These couples are a combination of gold alloyed with 0.02–0.03 per cent iron together with chromel or a semi-conductor as the opposite element. The thermocouple sensitivity over the whole range is never less than 10 $\mu\text{V}/^\circ\text{C}$ and temperature differences of 0.001° C can be measured to a few per cent. By this means it has

been possible to study solid helium in the body-centred cubic phase which exists only over a temperature range of a few hundredths of a degree. The method is also being applied to measurements on lithium fluoride using different concentrations of the ^6Li and ^7Li isotopes, in order to obtain a better understanding of the effects of phonon scattering.

In the two sessions devoted to fluids it soon became apparent that there was a division of interests between precise and practical requirements. B. Vodar (Centre National de la Recherche Scientifique, Bellevue) and his collaborators satisfied those delegates interested in the former by describing several new methods together with their results estimated to be accurate to 1 per cent for a series of gases and liquids over a 600° C temperature range and pressures up to 1,000 bars. There is, however, a very great interest in quick and reliable methods capable of yielding the more practical accuracies of 5–10 per cent. The thermal comparator method developed by R. W. Powell (National Physical Laboratory) and others, and the hot-wire method as suggested by D. T. Jamieson (National Engineering Laboratory), are two which should fulfil these needs. The whole subject of thermal conductivity of liquids is overshadowed by the very large discrepancies in the results that are available for a number of liquids in general use. H. Poltz (Physikalisch-Technische Bundesanstalt, Braunschweig), in discussing the effects of radiation in liquids, has found that the effective conductivity is dependent on the optical thickness of a liquid layer. There are measurable contributions due to this mode of heat transfer even at room temperature. It is possible that this radiation effect, if studied further, may well be a significant contribution towards resolving the existing divergencies which cannot as yet be fully explained.

The design and efficient operation of nuclear reactors are greatly dependent on a knowledge of the thermal properties of the materials used. These facts were emphasized in three contributions devoted to materials at present in use and two dealing with those for advanced reactors. Results for post-irradiated uranium, UO_2 , during neutron irradiation and *Dragon* fuel cartridge materials were presented by D. Shaw, D. J. Clough and J. Milne (U.K. Atomic Energy Authority), respectively, and were supplemented by McElroy's (Oak Ridge National Laboratory) two reports, one on graphite materials to 1,000° C and the other dealing with UO_2 to 400° C. The borides and nitrides of Ti, Zr, Hf and Nb are now being considered as high-temperature materials of the future, and recent work has shown that they have valuable practical physical properties coupled with unusual electronic and lattice conductivity behaviour which have yet to be fully explained. R. Mendez-Penalosa (University of Madrid) discussed his work on zirconium nitride, and M. Hoch (Cincinnati University) presented results for a collection of these materials up to 1,800° C obtained using an inductive heating method. The evaluation of thermal conductivity required an accurate knowledge of emissivity and specific heat, which in this case were independently measured. This last-mentioned factor served to highlight the controversy that existed during several sessions whereby the relative merits of the measurement of thermal conductivity, as opposed to its evaluation from thermal diffusivity determinations, were elaborated. G. C. Danielson (Iowa State University) has indicated that

there is no doubt that thermal diffusivity can be measured both accurately and quickly. However, the derivation of thermal conductivity from this measured quantity is still dependent on an accurate knowledge of specific heat and density.

Since 1961 there have been three informal conferences restricted mainly to workers concentrated on the North American continent and devoted almost entirely to solid materials. The growth of the work has been sufficient to justify an international meeting which covered the subject more comprehensively. General benefit has resulted from the exchange of information concerning the problems and the anticipation of future requirements. However, it

would appear that there are two important matters which workers in the field should settle without delay. The first point relates to the standardization of units and symbols, a case where physicists, engineers and chemists must co-operate before the number of units exceeds the number of methods. Secondly, there is an international requirement for the production and property evaluation of reliable and reproducible reference materials for a very wide range of thermal conductivity and temperature.

Abstracts of all the papers presented are available on application to the Basic Physics Division, National Physical Laboratory.

R. P. TYE

SPACED-SITE OBSERVATIONS OF JUPITER IN 1963

By C. H. BARROW and G. M. RESCH

Department of Physics, Florida State University, Tallahassee, U.S.A.

F. W. HYDE

Radio Astronomy Observatory, St. Osyth, Essex, Great Britain

AND

G. M. GRUBER and M. C. BOSCH

Department of Physics, Rhodes University, Grahamstown, South Africa

JUPITER has been monitored at 18 Mc/s for 16 h daily during 133 days in 1963. This was achieved by combining observations from three stations in the United States, in Great Britain and in South Africa. Correlation coefficients between Jupiter activity and various indicators of solar activity have been computed, but these do not indicate any statistically significant cross correlation. The occurrence probability of the Jupiter radiation was found to differ considerably at each site.

It has been suggested by several investigators that the radiation from Jupiter is in some manner related to solar activity, in that periods of Jupiter activity frequently follow periods of solar activity within a few days. This effect was first reported by Warwick¹ and has also been observed by Carr *et al.*², by Douglas³, and by Barrow⁴. There is, however, no general agreement as to an average delay time between periods of solar activity and possible related periods of Jupiter activity, estimates of from two to ten days having been proposed by the various investigators.

Roberts⁵, using data obtained in 1960 by Carr *et al.*², computed the correlation coefficient between Jupiter activity and geomagnetic activity index A_p . A peak corresponding to a delay of eight days was indicated, but at the same time another peak of comparable significance indicated a negative delay of eight days, that is, for geomagnetic activity after Jupiter activity. Roberts mentions similarly inconclusive unpublished results obtained by Higgins and concludes that all the apparent correlations observed so far may be merely statistical fluctuations.

If the phenomena are in fact related, there are two possible explanations of these different results. Either the statistics are unsound, due to the fact that insufficient Jupiter observing time was available daily for comparison with solar activity, or else the relationship between the two phenomena is too complex to be expressed by a simple cause-and-effect explanation. A preliminary investigation of the former possibility was conducted during 1963 by Florida State University Radio Observatory in collaboration with observatories in Great Britain and in South Africa.

The experiment was simply to record the radiation from Jupiter for as long as possible each day and to compare the periods of Jupiter activity with periods of solar activity as indicated by flares, 10-cm solar radiation, sunspots, and

geomagnetic activity. The Sun can be observed from somewhere on the Earth almost 24 h daily, whereas most Jupiter observers are limited to some 4–8 h according to their aerial systems. The daily period of observation of Jupiter was, therefore, increased to some extent by combining observations made at two additional sites, in Great Britain and in South Africa, with results obtained at Tallahassee. The locations of the sites, the corresponding altitudes of Jupiter at meridian transit and the aerials used are shown in Table 1. The combined observations from the three sites operating in tandem amounted to some 16 h continuous monitoring each night, a period corresponding to about $1\frac{1}{2}$ rotations of Jupiter.

Table 1. LOCATIONS OF THE THREE STATIONS MONITORING JUPITER DURING THE 1963 APPARITION

Site	Latitude	Longitude	Altitude of Jupiter at transit	Aerial
Tallahassee	30° 27' N.	84° 18' W.	64° S.	Square corner reflector
St. Osyth	51° 47' N.	01° 02' E.	42° S.	Square corner reflector
Grahamstown	33° 19' S.	26° 26' E.	53° N.	Single dipole and eight dipole array

The aerial-receiver-recorder systems were identical at Tallahassee and at St. Osyth. Each consisted of a square corner reflector containing a single folded half-wave dipole fed to a commercial short-wave communications receiver. The bandwidth of the receiver was about 5 kc/s and the recorder constant was 0.25 sec. All the observations at these two sites were monitored following the procedure given recently by Barrow⁶.

At Rhodes University a single folded dipole was used in conjunction with a broadside array of eight dipoles at another site some 100 miles away. The receiver bandwidth was 8 kc/s and the recorder constant was 0.8 sec. Some of the observations were monitored, but identification was also based on a comparison of the records taken at the two sites. The total observing time amounted to about 70 per cent of that at Tallahassee or at St. Osyth.

The first co-ordinated period of observation by all three sites was July 17–November 25, 1963. The combined observations are shown in a histogram in Fig. 1. The histogram has been compiled in terms of 'numbers of events' rather than 'occurrence probability', as the occurrence probability was found to be different at each site.