GAS CHROMATOGRAPHY

AN informal symposium organized by the Ministry of Technology was held on May 31 at the Paisley College of Technology, Paisley, with Mr. A. F. Williams in the chair. The participants were welcomed on behalf of the College by the principal, H. N. Henry.

The first paper was given by Mr. G. R. Jamieson (Paisley College of Technology) on "Gas-Solid Chromatography using Adsorbents with Modified Surfaces". He first pointed out that the advances in gas-solid chromatography had been much less spectacular than those in gas-liquid chromatography but, during the past two years, an increasing number of investigations using gas-solid chromatography had been reported in the literature. Possibly one of the main reasons for this renewal of interest was that with the advent of sensitive ionization detectors, there was now no major difficulty in operating in the linear range of the adsorption isotherm. He then went on to say that although gas-liquid chromatography was, at the moment, more versatile than gas-solid chromatography, the latter method had two potential advantages: (1) the great potential selectivity of the adsorption process; (2) the sharper resolution that should be attainable and thus the greater speed of separations. Various illustrations of these advantages were given: (1) separation of methylpyridines on alkali metal nitrate columns; (2) separations on various inorganic salt columns operated at 38° C; (3) separations on porous layer glass beads-metal oxide columns; (4) separations of quaterphenyls and hexaphenyls on lithium chloride and caesium chloride columns.

Mr. Jamieson next described some separations which he had carried out on various alumina columns. He showed how the retention indices of benzene and alkenes varied depending on the pretreatment temperature of the alumina, and also how, using small sample sizes, well-shaped peaks were easily obtainable. The effect on the retention indices of the foregoing compounds of modifying the surface of the alumina with different sodium halides was described, and he showed that column characteristics could be altered by changing the anion, by either slurring the alumina with the halide or by mixing dry, and by varying the pretreatment temperature of the alumina before modifying the surface with the halide. The effects of using silica instead of alumina were next described and also the results obtained by butylating the silica.

The final point made by Mr. Jamieson was that the use of liquid crystals as stationary phases offered a field of investigation. Liquid crystals behave mechanically as liquids, but they preserve some of the order of crystalline solids. Taking *p*-azoxyanisole as an example, he said that this compound in the nematic state would be expected to show a selective affinity for linear molecules and on a 4 ft. × 0.25 in. column of *p*-azoxyanisole on 'Celite' he was able to separate the isomeric bromotoluenes, the expected order of emergence, *ortho*, *meta*, *para*, being realized.

Mr. Jamieson then took the chair for the second paper, which was given by Mr. A. F. Williams (Imperial Chemical Industries, Ltd., Nobel Division) on "Techniques for Quantitative Gas Chromatography; the Analysis of Cellulose Ethers and Nitroglycerine". Mr. Williams first discussed quantitative gas chromatography in terms of sample addition, the detector and the use of peak heights or peak areas for calculation of results. The katharometer and flame ionization detectors were considered to be the most widely used detectors for quantitative work in the general field of organic analysis. When the katharometer was used for detection, careful control of the amount of sample going on to the column was essential because the detector is linear only over a limited range of concentration. This degree of control was much more important when

nitrogen was used as carrier gas than when helium or hydrogen was used and also varied with the composition of the sample and its type. It was therefore usually necessary to carry out two determinations if accurate results are required, although this depends to some extent on the nature of the sample. When the flame ionization detector was used, considerably more latitude concerning the amount of load may be taken, although the amount of sample used for analysis is the order of a factor of 100–1,000 times less than that used in conjunction with katharometers. No evidence was obtained to show that the use of peak areas instead of peak heights led to more accurate results. A detailed examination of the results obtained using both types of detector for the analysis of a simple benzene, toluene and xylene mixture has been carried out and the effects of load, using a splitting procedure and changes in electrode gap, were illustrated. It was concluded that the flame ionization detector was more useful than the katharometer for quantitative work.

Mr. Williams concluded his paper by illustrating the application of the flame ionization detector to the analysis of mixtures of nitroglycerine, ethylene glycol dinitrate and nitrotoluenes, and also to the rapid determination of alkoxy groups both in simple ethers and also in cellulose ethers.

A considerable amount of discussion followed Mr. Williams's paper about the relative merits of the use of 'peak heights' and 'peak areas' for quantitative analysis and of the problems which arise in the quantitative analysis of mixtures of biochemical origin when the components can be identified, but no pure standards are available for quantitative calibration purposes.

The third paper was given by Dr. F. L. Mitchell (Royal Infirmary, Edinburgh) on "Gas Chromatography of Radioactive Substances". He said that with the increasing use of radioactive isotopes in chemistry and biochemistry, it is important that such a powerful analytical tool as gas chromatography should incorporate a sensitive device for the detection and measurement of radioactivity. Various techniques have been tried, including scintillation counting of continuously collected zones from the column, and gas-flow proportional counting, working at both column and room temperature.

A technique based on that of James and Piper (1961) has been developed commercially and has proved very satisfactory for the counting of carbon-14 and tritium. Before passing through a gas-flow counter at room temperature, the column effluent is first subjected to oxidation and reduction by passing the gas at 800° over cupric oxide followed by iron filings. The argon then contains only hydrogen and carbon dioxide from the organic material originally present, and 4–5 per cent of dry carbon dioxide is added to the stream to produce a suitable gas for proportional counting. The gas-flow counter consists of a metal tube of approximately 10 ml. capacity with a fine stainless-steel wire stretched longitudinally from end to end. After amplification, the output from the counter is fed to a ratemeter which displays on the recorder either the rate at which the pulses are arriving, or the integral of their total. By using the integrator 5 mμc. can easily be detected and measured. The gas stream from the column may be split, one part passing through the normally used detector while the other is directed through the counter, or the whole may be passed through the counter after passing through a conventional closed detector such as that using argon ionization.

Separation by gas chromatography, with simultaneous detection of the zones by both normal techniques and radioactive measurement, has proved useful to the biochemist in the examination of biosynthetic pathways, to the isotope manufacturer for establishing the purity of

labelled compounds, and to the chemist whenever information on the fate of a particular compound during a complex chemical reaction is required.

Mr. J. Wight (University of Strathclyde) read a paper on "The Examination of Food Volatiles by Gas Chromatography". He said that what we term 'flavour' is a combination of taste, smell or aroma, and the 'feel' of the food in the mouth. Of these the aroma is by far the most important and, since this depends on the presence—usually in minute amounts—of certain volatile compounds, the advantages of gas chromatography in aroma investigations become apparent. There are few gas-chromatographic techniques special to these investigations, and the main difficulties lie with the collection and concentration of the volatiles and with the identification of the components. Where large quantities of food have to be stripped of their volatiles, for example, by distillation, steam or nitrogen stripping, care must be taken to avoid loss or change; high-temperature treatment will almost certainly result in the production of artefacts.

Separation and identification are complicated by the large number of components present, the presence of chemically dissimilar classes of compounds and the wide range of retention times. Use must be made of techniques other than gas chromatography, and recently the mass spectrometer has proved to be a most powerful aid to identification.

There are many distinct applications of gas chromatography, for example, the general study of aroma volatiles, the production of aroma by cooking or processing, the investigation of flavour defects of stored foods and the quality control of materials such as essential oils.

It must be remembered that the results obtained by gas chromatography are essentially analytical and that these results have still to be interpreted in terms of

aroma. In the absence of sufficient data on threshold values both of pure substances and of mixtures, it is important that the analytical work be supported by flavour panels. The aroma as sensed by the nose is, after all, the final criterion. Mr. Wight concluded his paper by showing chromatograms obtained from the volatiles of various common foodstuffs.

The final paper was read by Mr. J. Craig Higgins (National Coal Board) on "Developments in the Technique of Mine Air Analysis by Gas Chromatography". Mr. Higgins first of all pointed out that for the special problems involved in mine air analysis, no commercial gas chromatograph had been found suitable and a gas chromatograph had been designed and constructed at the laboratories of the National Coal Board.

He then went on to give a very full description of this gas chromatograph, which was a dual-column instrument but not in the usual sense of the meaning of dual column. Two different column packings were used, 'Molecular Sieve 5X' and silica gel, and detection was by thermal conductivity cells. By means of a special valve system, samples of the gas to be analysed were put on to both columns simultaneously and flow rates were adjusted so that the components from one column were recorded before the components started to emerge from the second column. In using this system a complete analysis of the mine gas could be recorded on the one chromatogram.

Mr. Higgins ended by showing how these chromatographs were used in the National Coal Board's mobile laboratories, and he pointed out that wherever possible duplication of equipment was essential to obviate any breakdown or failure of components in these mobile laboratories.

The symposium concluded with an address by Mr. A. C. Low of the Ministry of Technology. G. R. JAMESON

CNIDARIA AND THEIR EVOLUTION

THE Zoological Society of London organized a symposium during March 3–4, at which evolution in the Cnidaria as well as many diverse aspects of this plastic group were reviewed and discussed.

Opening the symposium, Prof. C. F. A. Pantin (Cambridge) gave a stimulating address on "Homology, Analogy and Chemical Identity". To the first two, he added "chemical identity", that is, resemblances which can be traced to the absolute similarity of each set of isotopes in the Periodic Table and of the molecules built from them. He indicated that chemical identity can give rise to packing phenomena, as in crystals, creating well-defined morphological features, far above the atomic level, which are, or partially only, the result of adaptive selection. The independent appearance of particular classes of molecule such as are found in pigments and other 'chemical building stones' arises from chemical identity. Much caution should therefore be adopted in using features of this kind as evidence of evolutionary relationship.

Prof. Pantin indicated that analogy arises because natural selection operates by setting the organism engineering specifications for each part that must be realized for survival. He regarded the longitudinal musculature of cnidarian polyps as an example of a weak specification allowing many solutions. On the other hand, rigid and detailed specifications like those responsible for close similarities in complex eyes are not evident in the Cnidaria.

Homologies of parts account for the most characteristic resemblances between animals, these homologies depending on a plan or archetype to which the structure of all species in the class may be referred. This archetype (which is not an ancestor) and its homologies he considered as a network of tissue relationships. Further, he thought the system as a whole met an engineering requirement and

that natural selection acted strongly against any serious departure from the network of tissue relationships. However, this network could be distorted to meet the needs of adaptive radiation, and as examples he quoted the different mesenteric patterns of the Anthozoa.

Dr. L. E. R. Picken and Dr. R. J. Skaer (Cambridge) gave a lucid review of researches on nematocysts and dealt comprehensively with the subject. Among other interesting items, the authors discussed a new aspect of nematocyst chemistry—phosphatases, 5-nucleotidase and cholinesterase. Several amino-acid analyses of nematocysts isolated in bulk are now available and something is known of certain other chemical components.

There was also a very interesting demonstration, from electron microscope investigations, that the wall of the undischarged thread in isorhizas of *Corynactis viridis* is pleated to form a triple screw and that the undischarged capsules have a 'notional' osmotic pressure up to approximately 140 atmospheres.

The authors believe that cnidoblasts may still be regarded as independent effectors although the excitation-threshold of the cnidocil–cnidoblast unit may be under nervous control in some instances, depending on the physiological condition of the animal. It also emerged that taxonomic investigations on the different kinds of nematocysts, based on the light microscope, are not enough and that further electron-microscope examinations are essential.

Dr. David Chapman (Halifax, Nova Scotia) developed some interesting ideas regarding the origins of the Scyphozoa from an examination of the anatomy of the scyphistoma of *Aurelia*. He was inclined to regard the fossil conulariids as ancestral to this group, basing his conclusions on certain puzzling features in the anatomy of the scyphistoma which could be explained by adopting