Figure 1 Development of sensory connections in the brain. **a**, The possible role of filopodia in synapse formation. The filopodial protrusion responds to an axon growing past by extending towards it. Having made contact, the protrusion retracts, and pre- and postsynaptic ultrastructural specializations form¹⁵. Lendvai *et al.*¹ have shown that the filopodia in the barrel cortex are less motile when sensory inputs from the whiskers are absent. **b**, The effect of whisker deprivation on the inputs and outputs of barrel cortex neurons. When the whiskers are trimmed, low levels of uncorrelated spontaneous activity arrive at the cortical neurons, so the mechanism for collecting correlated inputs does not work. The neurons are envisaged to require a minimum number of like inputs to drive an output. The outputs are therefore weak (or zero as shown here). With normal whisker input, the highly correlated activity allows the correlation detector to sort the inputs into like sets. An output can now be produced by convergence of activity from a single whisker (D1 in the case illustrated).

synchronously activated synapses would be selected to drive the neuron to fire action potentials, and responses would be weak (Fig. 1b).

How could sensory activity control spine motility? It is possible that sensory activity controls presynaptic motility and that the postsynaptic spines move in response to the number of new axons growing near them. In this case, filopodial motility would be a function of presynaptic motility. Alternatively, if the presynaptic elements are just as active with or without sensory input, it raises the problem of how the postsynaptic cells sense the decrease in sensory input at a stage in development when the neuron has formed only a few of its synapses. In this case, it is possible that the rate of synapse acquisition is normal, but few new connections are rejected, producing low synapse turnover. To answer these questions it will be important to visualize the presynaptic inputs at the same time as the spines. Finally, it will be of interest to know whether the process of synapse turnover described here for the

developing brain is also responsible for plasticity in the adult barrel cortex¹⁴.

Kevin Fox is at the Cardiff School of Biosciences, Cardiff University, Museum Avenue, Cardiff CF10 3US, UK.

e-mail: foxkd@cardiff.ac.uk

1. Lendvai, B., Stern, E. A., Chen, B. & Svoboda, K. *Nature* **404**, 876–881 (2000).
2. Verhage, M. *et al. Science* **287**, 864–869 (2000).
3. Fox, K. J. *Neurosci.* **12**, 1826–1838 (1992).
4. Hubel, D. H., Wiesel, T. N. & LeVay, S. *Phil. Trans. R. Soc. Lond. B* **278**, 377–409 (1977).
5. Miller, K. D., Keller, J. B. & Stryker, M. P. *Science* **245**, 605–615 (1989).
6. Killackey, H. P., Belford, G., Ryugo, R. & Ryugo, D. K. *Brain Res.* **104**, 309–315 (1976).
7. Antonini, A. & Stryker, M. P. *Science* **260**, 1819–1821 (1993).
8. Denk, W. & Svoboda, K. *Neuron* **18**, 351–357 (1997).
9. Woolsey, T. A. & Van der Loos, H. *Brain Res.* **17**, 205–242 (1970).
10. Fox, K., Schlaggar, B. L., Glazewski, S. & O'Leary, D. M. M. *Proc. Natl Acad. Sci. USA* **93**, 5584–5589 (1996).
11. Fox, K. in *Progress in Brain Research* (eds Mize, R. R. & Erzurumlu, R.) 219–234 (Elsevier, Amsterdam, 1996).
12. Isaac, J. T., Crair, M. C., Nicoll, R. A. & Malenka, R. C. *Neuron* **18**, 269–280 (1997).
13. Constantine-Paton, M., Cline, H. T. & Debski, E. *Annu. Rev. Neurosci.* **13**, 129–154 (1990).
14. Glazewski, S., Chen, C.-H., Silva, A. & Fox, K. *Science* **272**, 421–423 (1996).
15. Smith, S. J. *Soc. Neurosci. Abstr.* **24**, 1002 (1998).

Daedalus

High tension

Fracture is the most catastrophic of mechanical failures. Daedalus is now developing a strategy against it. Imagine, he says, a fine steel wire loaded to breaking point, but carrying a current maintained by a driving voltage (maybe 10 volts). At the instant of fracture, the whole of this voltage will appear across the snapped ends of the wire. When they have separated by a nanometre, say, the electric field across the gap will be 10 billion volts per metre — a field whose attractive force exceeds the breaking strain of steel. So the broken ends will be attracted back together again, and welded by the resulting discharge. The wire will not fracture.

Sadly, a thick component cannot be protected this way. The guard current would simply detour around a spreading crack. An anisotropic conductor is needed, conducting in the direction of the applied stress, but insulating at right angles to it. The current would then be unable to flow sideways round an incipient fracture. The slightest momentary flaw would experience an immediate healing attractive force.

Anisotropic conductors are hard to come by. Polyacetylenes and platinum-chain compounds would be awkward constructional materials; carbon nanotubes would be outstanding but are not yet available in the metre lengths needed for serious engineering. A bundle of metal wires, glued together by an insulating cement into a shaped component, might work well. So might a bundle of silica tubes filled with metal, drawn out to sub-micrometre diameter, and cemented or annealed together.

Such costly fabrications would be limited to advanced and crucial uses, such as helicopter rotor blades and aerospace components. Their easy integration into an electronic control system could transform the state of the art. Wired into the master computer, they would act as multiple strain gauges, allowing the stress in every filament of the structure to be monitored in real time. An aircraft or space vehicle under such total computer surveillance could be manoeuvred with unprecedented insight and strategy. Every component could be loaded reliably to the plastic-flow limit, with no factors of safety to allow for ignorance: every stress would be known. If the current failed, of course, the whole thing would fall to pieces at once. But such an advanced craft would be doomed by computer failure anyway.

David Jones

The Further Inventions of Daedalus is published by Oxford University Press.