

TERAHERTZ WAVEPLATES

Paper option

A simple stack of ordinary white paper can be used as a high-quality polarization waveplate for the terahertz spectral region, according to researchers in Germany and the USA (*Opt. Express* **19**, 24884–24889; 2011).

Benedikt Scherger and co-workers from Philipps Universität Marburg, University of Arizona and the University of Colorado cut standard office paper (120 μm thick and with a weight of 80 g m^{-2}) into strips and stacked them with alternating air gaps formed by spacers. They then used a clamp or rubber bands to hold the resulting stack of 150–200 paper–air pairs in position.

Characterization of the stack's properties in the terahertz region revealed that it was strongly birefringent, with refractive indices of 1.295 and 1.149 for p- and s-polarized light, respectively, at a frequency of 0.244 THz. This allowed



© 2011 OSA

the stack to rotate the polarization of incident terahertz light and thus function as a waveplate.

By placing the paper stack between traditional wire grid polarizers, the researchers were able to make transfer function measurements of the paper waveplate's performance. Data show that transmission contrast ratios as high as 40 dB are possible, suggesting that the waveplate can rotate a linear polarization

state as well as output a pure polarization state, with negligible depolarizing.

The behaviour of the stack was not perfect: it exhibited polarization-dependent loss, with s- and p-polarizations experiencing different levels of attenuation. For frequencies of around 0.25 THz, however, the overall transmission losses due to absorption were less than 5 dB.

"These waveplates have the advantage of being extremely cheap and easy to fabricate," comment the authors of the study. "They show excellent performance at their design frequency."

The researchers are now thinking of constructing paper achromatic waveplates for operation over wider bandwidths based on the use of multiple plates of varying thickness.

OLIVER GRAYDON

QUANTUM OPTICS

Correlations on a chip

Researchers have developed a semiconductor structure capable of supporting quantum correlations between photons and strong single-photon nonlinearities, thus paving the way for the development of chip-based devices for quantum secure communications and quantum information processing.

XinAn Xu and Chee Wei Wong

Cavity quantum electrodynamics describes the behaviour of a quantum emitter inside an optical cavity, and is one of the few realizable experimental systems in which the coherent interaction between the emitter and the cavity mode can exceed dissipative and dephasing processes. Recent advances in this field include the observation of vacuum Rabi splitting^{1–3}, interference⁴, upconversion⁵ and the metasurface enhancement⁶ of single photons, as well as cavity–exciton photon blockade and tunnelling⁷ on a semiconductor chip. In addition, by varying the local density of optical states to control spontaneous emission, researchers have demonstrated highly efficient quantum dot single-photon sources with sub-Poissonian statistics⁸.

Now, writing in *Nature Photonics*, Reinhard *et al.*⁹ report strong photon–photon quantum correlations on the first and second Jaynes–Cummings manifolds for a

single quantum dot coupled to a photonic crystal nanocavity, even in the presence of quantum dot blinking. The behaviour of a two-level quantum emitter–cavity system is described by the Jaynes–Cummings standard model^{10,11}, in which spontaneous emission can be controlled through coherent atom–vacuum field interactions. The quantum emitter–cavity system is described by the Rabi interaction rate g , the quantum emitter decoherence or decay rate γ , and the cavity photon decay rate κ . In the weak coupling regime, the emitter or the cavity photon decay rate is greater than the Rabi interaction rate. There is an irreversible energy exchange between the emitter and the cavity photon, with a Purcell-modified spontaneous emission rate that is based on the local density of states.

In the strong coupling regime, the Rabi interaction rate exceeds the cavity or quantum emitter decay rate, with reversible

spontaneous emission and multiple re-absorption/re-emission oscillations between the emitter and the cavity mode. The resulting strongly coupled open system exhibits the solid-state analogue of vacuum Rabi splitting with normal-mode splitting in the spectral domain, and is significantly perturbed by the detection event¹⁰, which collapses the wavefunction and causes the second-order correlation function at zero time delay, $g^{(2)}(0)$, to tend to zero. This is understood as the stochastic renormalization of the cavity emission rate after the first photon emission, which has strong photon antibunching character.

The exciton–photon polariton energy ladder displays distinct anharmonicity. When probed on the second rung of the Jaynes–Cummings ladder, the strongly coupled polariton system can exhibit photon bunching, thereby providing optical nonlinearities at the few-photon level that