Quantum process tomography of a universal entangling gate implemented with Josephson phase qubits

R. C. Bialczak, M. Ansmann, M. Hofheinz, E. Lucero, M. Neeley, A. D. O'Connell, D. Sank, H. Wang, J. Wenner, M. Steffen[†], A. N. Cleland and J. M. Martinis[★]

Quantum gates must perform reliably when operating on standard input basis states and on complex superpositions thereof. Experiments using superconducting qubits have validated truth tables for particular implementations of, for example, the controlled-NOT gate^{1,2}, but have not fully characterized gate operation for arbitrary superpositions of input states. Here we demonstrate the use of quantum process tomography^{3,4} (QPT) to fully characterize the performance of a universal entangling gate between two superconducting qubits. Process tomography permits complete gate analysis, but requires precise preparation of arbitrary input states, control over the subsequent qubit interaction and ideally simultaneous single-shot measurement of output states. In recent work, it has been proposed to use QPT to probe noise properties⁵ and time dynamics⁶ of qubit systems and to apply techniques from control theory to create scalable qubit benchmarking protocols^{7,8}. We use QPT to measure the fidelity and noise properties⁵ of an entangling gate. In addition to demonstrating a promising fidelity, our entangling gate has an on-to-off ratio of 300, a level of adjustable coupling that will become a requirement for future high-fidelity devices. This is the first solid-state demonstration of QPT in a two-qubit system, as QPT has previously been demonstrated only with single solid-state qubits^{9–11}.

Universal quantum gates are the key elements in a quantum computer, as they provide the fundamental building blocks for encoding complex algorithms and operations. Single-qubit rotations together with the two-qubit controlled-NOT (CNOT) are known to provide a universal set of gates¹². Here, we present the complete characterization of a universal entangling gate, the square root of *i*-SWAP (SQiSW; ref. 13), from which gates such as the CNOT can be constructed. The pulse sequence for a CNOT can be written in terms of a SQiSW gate as follows: CNOT = $R_y^A(-90^\circ)[R_x^A(90^\circ) \otimes R_x^B(-90^\circ)]$ SQiSW $R_x^A(180^\circ)$ SQiSW $R_y^A(90^\circ)$, where $R_j^\alpha(\theta)$ is a rotation about axis $j = x, y, z$ by an angle θ on qubit $\alpha = A, B$. The SQiSW is a 'natural' two-qubit gate, as it directly results from capacitive coupling of superconducting qubits, yielding qubit coupling of the general form $\sigma_{Ax}\sigma_{Bx}$ or $\sigma_{Ay}\sigma_{By}$, where $\sigma_{x,y}$ are the Pauli spin operators for qubits A and B (refs 14,15). Under the rotating-wave approximation, the corresponding interaction Hamiltonian has the form $H_{\text{int}} = \hbar(g/2)(|01\rangle\langle 10| + |10\rangle\langle 01|)$, where $|01\rangle = |0\rangle_A \otimes |1\rangle_B$ and g is the coupling strength that depends on design parameters.

When the two qubits are placed on-resonance, the two-qubit states are coupled by H_{int} as shown in Fig. 1a. The amplitudes of

these states then oscillate in time, as described (in the rotating frame) by the unitary transformation

$$U_{\text{int}} = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos(gt/2) & -i\sin(gt/2) & 0 \\ 0 & -i\sin(gt/2) & \cos(gt/2) & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

where t is the interaction time and the representation is in the two-qubit basis set $\{|00\rangle, |01\rangle, |10\rangle, |11\rangle\}$. For an interaction time $gt = \pi$, the state amplitudes are swapped, such that $|01\rangle \rightarrow -i|10\rangle$ and $|10\rangle \rightarrow -i|01\rangle$. The SQiSW gate is formed by coupling for one-half this time, $gt = \pi/2$, producing cosine and sine matrix elements with equal magnitudes, thus entangling the qubits. When the qubits are off-resonance by an energy $|\Delta| \gg g$ (Fig. 1b), the off-diagonal elements in U_{int} are small and have average amplitude g/Δ , effectively turning off the qubit–qubit interaction.

The electrical circuit for the capacitively coupled Josephson phase qubits^{16,17} used in this experiment is shown in Fig. 1c. Each phase qubit is a nonlinear resonator built from a Josephson inductance and an external shunting capacitance. When biased close to the critical current, the junction and its parallel loop inductance L give rise to a cubic potential with energy eigenstates that are unequally spaced. The two lowest levels are used as the qubit states $|0\rangle$ and $|1\rangle$, with transition frequency ω_{10} . This frequency can be adjusted independently for each qubit through the bias current $I_{\text{bias}}^{A,B}$. Each qubit's state is detected through a single-shot measurement^{18,19}, using a fast pulse $I_Z^{A,B}$ combined with read-out using an on-chip superconducting quantum interference device.

State preparation and tomography use single-qubit logic operations, corresponding to rotations about the x, y and z axes of the Bloch sphere¹⁹. Rotations about the z axis are produced by fast ($\sim$ nanosecond) current pulses $I_Z^{A,B}(t)$, which adiabatically change the qubit frequency, turning on and off the interaction and leading to phase accumulation between the $|0\rangle$ and $|1\rangle$ states. Rotations about any axis in the x – y plane are produced by microwave pulses resonant with each qubit's transition frequency, applied through $I_{\text{mw}}^{A,B}(t)$. The phase of the microwave pulses defines the rotation axis in the x – y plane, and the pulse duration and amplitude control the rotation angle. In previous work²⁰, such single-qubit gates were shown to have fidelities of 98%, limited by the energy relaxation T_1 and dephasing T_2 times, which for this device were measured to be 400 and 120 ns, respectively.

Department of Physics, University of California, Santa Barbara, California 93106, USA. [†]Present address: IBM T.J. Watson Research Center, Yorktown, New York 10598, USA. [★]e-mail: martinis@physics.ucsb.edu.

Figure 1 | Bloch-sphere, energy-level and circuit representations of the device. **a,b**, Energy-level diagram with coupling interaction turned on (**a**) and off (**b**). **a**, When qubits are on-resonance ($\Delta = 0$), their interaction swaps the populations of the $|01\rangle$ and $|10\rangle$ states at a frequency given by the coupling strength g . The Bloch-sphere representation of the $|01\rangle$ and $|10\rangle$ subspace shows state rotation (dashed line) about the x axis resulting from the interaction g . **b**, When off-resonance $|\Delta| \gg g$, qubit swapping (dashed line) is effectively turned off. **c**, Electrical schematic for capacitively coupled phase qubits. Each qubit junction (single cross) with critical current I_0 is shunted by an external capacitor C and inductor L . An interdigitated capacitor $C_c \sim 2$ fF couples the qubits, yielding an interaction $g/2\pi = 11$ MHz. Qubit bias is through I_{bias} , microwave control through $I_{\mu\text{w}}$ and qubit readout is carried out using a three-junction superconducting quantum interference device (three crosses) read out by V_{SQ} . Fast pulses on the I_z lines bias the qubits on- and off-resonance.

Figure 2 | Characterization of coupling interaction and measurement of on/off ratio. **a**, Sequence of operations: the $|10\rangle$ state is prepared by applying a 16-ns π -pulse to qubit A, and immediately followed by a fast pulse I_z^B that places qubit B close to resonance with qubit A (detuning Δ). After the qubits interact for a time t_f , the state occupation probabilities for each qubit are measured simultaneously. **b**, Measured occupation probabilities P_{10} and P_{01} versus detuning Δ and interaction time t_f . The oscillation period at $\Delta = 0$ yields the measured coupling $g/2\pi = 11$ MHz. Data were taken up to a maximum detuning of 200 MHz, but only up to 100 MHz is shown. The amplitude of oscillations decreases with detuning as expected. **c**, Peak-to-peak swapping amplitude versus detuning Δ , plotted with the predicted dependence $g^2/(g^2 + \Delta^2)$. The vertical scale for $g^2/(g^2 + \Delta^2)$ is adjusted to match the on-resonance amplitude at $\Delta = 0$. Determination of the swapping probability is limited to $>6 \times 10^{-2}$ by measurement noise. The calculated on/off ratio is indicated by the vertical arrow.

The experimental design was chosen to give qubit frequencies $\omega_{10}^{A,B}/2\pi \cong 5.5$ GHz. The strength of the coupling $g = (C_c/C)\omega_{10}^{A,B}$ was set by the coupling and qubit capacitances $C_c \approx 2$ fF and $C \approx 1$ pF, respectively. The coupling interaction is turned on and off by changing the relative qubit frequency $\Delta = \omega_{10}^A - \omega_{10}^B$ through an adjustment of the qubit B bias I_{bias}^B . A large detuning of $\Delta_{\text{off}}/2\pi \approx 200$ MHz was used to turn off the gate, yielding a small amplitude in the off-diagonal coupling $g/\Delta_{\text{off}} \approx 0.055$.

We first characterize the coupling by measuring the time dynamics of the entangling swap operation $|01\rangle \leftrightarrow |10\rangle$ as shown in Fig. 2a. Initially, both qubits are tuned off-resonance by 200 MHz and allowed to relax to the $|00\rangle$ state. A π pulse on qubit A then produces the $|10\rangle$ state. A current pulse $I_z^B(t)$ applied to I_{bias}^B brings the qubits within a frequency Δ of resonance. After an interaction time t_f , the bias I_z^B is reset to the original 200 MHz detuning and both qubits are then measured. Averaging

The amplitude of the swapping oscillations decreases with detuning as expected. In Fig. 2c we plot the peak-to-peak change in swap probability as a function of detuning Δ , compared to the theoretical prediction. Apart from a small reduction in the amplitude arising from imperfect measurement fidelity, the data is in good agreement with theory. At detunings $|\Delta|/2\pi > 50$ MHz, the swap amplitude is small and cannot be distinguished from the noise floor. From the maximum detuning bias of $\Delta/2\pi = 200$ MHz and from the coupling strength $g/2\pi = 11$ MHz obtained from spectroscopy measurements and the data in Fig. 2b, we compute the probability ratio $(\Delta/g)^2 = (200/11)^2 = 300$ as a figure of merit for the on/off coupling ratio.

411

Figure 4 | Real and imaginary parts of the reconstructed χ matrix for the SQiSW gate, obtained from 16 possible input states

$\{|0\rangle, |1\rangle, |0\rangle + |1\rangle, |0\rangle + i|1\rangle\} \otimes \{|0\rangle, |1\rangle, |0\rangle + |1\rangle, |0\rangle + i|1\rangle\}$. Physical estimates to the experimental data are shown as solid bars. The transparent bars give the theoretically expected χ matrix, which does not include effects resulting from decoherence. Calibrations from measurement were accounted for in this analysis. Technical details regarding calibrations and the physical estimation can be found in the Supplementary Information. The matrix elements of χ_m^p that are non-zero because of energy relaxation and dephasing are marked with an asterisk and a circle, respectively.

In a QPT experiment^{22–24} errors arise from the entangling gate and errors in measurement. As we are interested in the quality of the entangling gate itself, we have calibrated out errors resulting from measurement¹⁸. As described in the Supplementary Information, measurement errors arise from both a misidentification of the $|0\rangle$ and $|1\rangle$ states, and measurement crosstalk, where a measurement of $|1\rangle$ in one qubit increases the probability of a $|1\rangle$ measurement in the second qubit¹⁸. By carrying out further calibration experiments, we are able to determine the probabilities for these errors and correct the probabilities of the $|00\rangle, |01\rangle, |10\rangle$ and $|11\rangle$ final states.

In addition, standard QPT typically produces an unphysical χ matrix because of inherent experimental noise^{22,24}. A physical χ matrix must be completely positive and trace preserving³ (CPTP), which implies it must have positive eigenvalues that sum to one. Our measured χ matrix has several negative eigenvalues, as discussed in the Supplementary Information. As is commonly done in QPT experiments^{22,24}, a χ matrix that satisfies the CPTP constraints must be obtained from the experimental data before the data can be compared to a theoretically predicted χ matrix, which is physical by construction. This can be computed by noting that QPT is essentially analogous to system identification from classical control theory. More specifically, the problem of finding a physical approximation to unphysical QPT data can be shown to be a convex optimization problem^{25,26}, a technique commonly used in control theory. We use a type of convex optimization called semidefinite programming²⁵ to find the physical χ matrix that best approximates our measured, unphysical χ matrix. Mathematically, for the experimentally obtained χ matrix and the physical approximation χ^p , we minimize the two-norm distance $\|\chi^p - \chi\|_2 \equiv \sqrt{\text{tr}\{(\chi^p - \chi)^2\}}$ with the constraints that χ^p be CPTP.

This physical matrix χ_m^p , which also includes the calibrations for measurement errors, is shown in Fig. 4. This matrix closely matches the original data before corrections for CPTP (see Supplementary Information). In both the real and imaginary parts of the χ_m^p matrix, we observe non-zero matrix elements in locations where such elements are expected, in qualitative agreement with the theory,

shown as the transparent bars. Quantitative comparison is obtained by calculating the process fidelity, $0 < F_p < 1$, which gives a measure of how close χ_m^p is to theoretical expectations²⁴. For the SQiSW gate demonstrated here, with measurement calibration taken into account, we find $F_p = \text{Tr}(\chi_t \chi_m^p) = 0.63$, where χ_t is the theoretical χ matrix for the SQiSW gate. χ_m and χ_e , the unphysical χ matrices with and without measurement calibrations, respectively, and χ_e^p , the physical approximation to the χ matrix that does not include the measurement calibrations, are shown in Supplementary Figs S1–S3.

Errors in our SQiSW gate primarily arise because the time for the experiment (~ 50 ns) is not significantly shorter than the T_2 dephasing time of 120 ns. This is confirmed using a recent theory⁵ by Kofman *et al.*, which includes the effects of dephasing and decoherence on the SQiSW χ matrix. In particular, the elements marked with an asterisk and a circle in Fig. 4 are non-zero because of energy relaxation and dephasing, respectively. The modified Pauli basis used here gives a sign change in the real part of $(\chi_m^p)_{XX,YY}$ and $(\chi_m^p)_{YY,XX}$, and the imaginary part of $(\chi_m^p)_{XX,II}$ and $(\chi_m^p)_{II,XX}$. Using this theory and the real part of $(\chi_m^p)_{IZ,IZ}$ and $(\chi_m^p)_{IZ,ZI}$, we estimate our single-qubit dephasing time as $T_2 = (3\pi + 2)/16g(\chi_m^p)_{IZ,IZ}$. From Fig. 4 we find $(\chi_m^p)_{IZ,IZ} = 0.105$ and $T_2 = 123$ ns, in close agreement with the value mentioned above obtained from Ramsey experiments. We also estimate the degree of correlation of the dephasing noise between the coupled qubits using $\kappa \approx (\chi_m^p)_{IZ,ZI}/[(\chi_m^p)_{IZ,IZ} - [(\pi - 2)/(3\pi + 2)]]$. Our measurement of $(\chi_m^p)_{IZ,ZI} \approx 0.017$ yields $\kappa \approx 0.11$, indicating that the dephasing is mostly uncorrelated. This is in agreement with previous work^{27–29} that found a dephasing mechanism local to the individual qubits.

Received 9 June 2009; accepted 3 March 2010; published online 25 April 2010

References

1. Plantenberg, J. H., de Groot, P. C., Harmans, C. J. & Mooij, J. E. Demonstration of controlled-NOT quantum gates on a pair of superconducting quantum bits. *Nature* **447**, 836–839 (2007).

2. Yamamoto, Y., Pashkin, Y. A., Astafiev, O., Nakamura, Y. & Tsai, J. S. Demonstration of conditional gate operation using superconducting charge qubits. *Nature* **425**, 941–944 (2003).
3. Chuang, I. L. & Nielsen, M. A. Prescription for experimental determination of the dynamics of a quantum black box. *J. Mod. Opt.* **44**, 2455–2467 (1997).
4. White, A. G. *et al.* Measuring controlled-NOT and two-qubit gate operation. *J. Opt. Soc. Am. B* **24**, 172–183 (2007).
5. Kofman, A. G. & Korotkov, A. N. Two-qubit decoherence mechanisms revealed via quantum process tomography. *Phys. Rev. A* **80**, 042103 (2009).
6. Wolf, M. M., Eisert, J., Cubitt, T. S. & Cirac, J. I. Assessing non-markovian quantum dynamics. *Phys. Rev. Lett.* **101**, 150402 (2008).
7. Kosut, R. L. Quantum process tomography via L1-norm minimization. Preprint at <http://arxiv.org/abs/0812.4323> (2009).
8. Mohseni, M., Rezaekhani, A. T. & Lidar, D. A. Quantum-process tomography: Resource analysis of different strategies. *Phys. Rev. A* **77**, 032322 (2008).
9. Howard, M. Quantum process tomography and Lindblad estimation of a solid-state qubit. *New J. Phys.* **8**, 33 (2006).
10. Chow, J. M. *et al.* Randomized benchmarking and process tomography for gate errors in a solid-state qubit. *Phys. Rev. Lett.* **102**, 090502 (2009).
11. Neeley, M. *et al.* Process tomography of quantum memory in a Josephson-phase qubit coupled to a two-level state. *Nature Phys.* **4**, 523–526 (2008).
12. Bremner, M. J. *et al.* Practical scheme for quantum computation with any two-qubit entangling gate. *Phys. Rev. Lett.* **89**, 247902 (2002).
13. Schuch, N. & Siewert, J. Natural two-qubit gate for quantum computation using the XY interaction. *Phys. Rev. A* **67**, 032301 (2003).
14. Wendin, G. & Shumeiko, V. S. Superconducting quantum circuits, qubits and computing. Preprint at <http://arxiv.org/abs/cond-mat/0508729> (2005).
15. Geller, M. R. *et al.* *NATO Science Series II: Mathematics, Physics and Chemistry: Quantum Computing With Superconductors I: Architectures* 171–194 (Springer, 2007).
16. You, J. Q. & Nori, F. Superconducting circuits and quantum information. *Phys. Today* **58**, 42–47 (2005).
17. Devoret, M. H. & Martinis, J. M. Implementing qubits with superconducting integrated circuits. *Quantum Inform. Process* **3**, 163–203 (2004).
18. McDermott, R. *et al.* Simultaneous state measurement of coupled Josephson phase qubits. *Science* **307**, 1299–1302 (2005).
19. Steffen, M. *et al.* Measurement of the entanglement of two superconducting qubits via state tomography. *Science* **313**, 1423–1425 (2006).
20. Lucero, E. *et al.* High-fidelity gates in a single Josephson qubit. *Phys. Rev. Lett.* **100**, 247001 (2008).
21. Liu, Y., Wei, L. F. & Nori, F. Quantum tomography for solid-state qubits. *Europhys. Lett.* **67**, 874–880 (2004).
22. Riebe, M. *et al.* Process tomography of ion trap quantum gates. *Phys. Rev. Lett.* **97**, 220407 (2006).
23. Childs, A. M., Chuang, I. L. & Leung, D. W. Realization of quantum process tomography in NMR. *Phys. Rev. A* **64**, 012314 (2001).
24. O'Brien, J. L. *et al.* Quantum process tomography of a controlled-not gate. *Phys. Rev. Lett.* **93**, 080502 (2004).
25. Boyd, S. & Vandenberghe, L. *Convex Optimization* (Cambridge Univ. Press, 2004).
26. Branderhorst, M. P. A., Nunn, J., Walmsley, I. A. & Kosut, R. L. Simplified quantum process tomography. *New J. Phys.* **11**, 115010 (2009).
27. Sendelbach, S. *et al.* Magnetism in SQUIDs at millikelvin temperatures. *Phys. Rev. Lett.* **100**, 227006 (2008).
28. Bialczak, R. C. *et al.* $1/f$ flux noise in Josephson phase qubits. *Phys. Rev. Lett.* **99**, 187006 (2007).
29. McDermott, R. Materials origins of decoherence in superconducting qubits. *IEEE Trans. Appl. Supercond.* **19**, 2–13 (2009).

Acknowledgements

Devices were made at the UCSB Nanofabrication Facility, a part of the NSF-funded National Nanotechnology Infrastructure Network. We thank A. N. Korotkov for discussions on parameter extraction from the χ matrix and J. Eisert for assistance on using convex optimization to approximate a physical χ matrix. Semidefinite programming convex optimization was carried out using the open-source MATLAB packages YALMIP and SeDuMi. This work was supported by IARPA (grant W911NF-04-1-0204) and by the NSF (grant CCF-0507227).

Author contributions

R.C.B. designed and fabricated the samples, designed and carried out experiments and analysed the data. R.C.B. co-wrote the paper with J.M.M. and A.N.C., who also supervised the project. M.A. and M.N. provided assistance with data-taking software. E.L. and M.H. provided assistance with data-taking electronics. M.S. provided assistance with data analysis. All authors contributed to experiment set-up, sample design or sample fabrication.

Additional information

The authors declare no competing financial interests. Supplementary information accompanies this paper on www.nature.com/naturephysics. Reprints and permissions information is available online at <http://npg.nature.com/reprintsandpermissions>. Correspondence and requests for materials should be addressed to J.M.M.