NEWS & VIEWS

Open Access

Stable and luminescent halide perovskite fabricated in water

Guangren Na¹ and Lijun Zhang¹

Abstract

Lead bromide perovskite nanoparticles are fabricated in the water, which has been recognized previously as a severe source of damage to halide perovskite materials and devices. The perovskite nanoparticles exhibit a high photoluminescence quantum yield and excellent material stability.

The past decade has witnessed the dramatic development of hybrid lead halide perovskites as promising semiconductors for applications in high-performance solar cells, photodetectors, light-emitting diodes, etc.¹. While the optoelectronic conversion efficiency of this family of intensively investigated materials has been persistently improved, there are several challenges standing in the way of their practical application. Although lead-derived toxicity is still a concern^{2–4}, poor stability is the most urgent problem confronting the halide perovskite research community^{5,6}. The manifestation of the poor stability includes the visible degradation of materials and devices exposed to room and high temperatures, illumination, oxidizing environments, and humidity^{7–10}, which is rooted in the not strong mixed ionic and covalent chemical bonding of halide perovskites.

To overcome the instability issue of halide perovskites, a few strategies have been developed, including A-site composition engineering, the addition of defect passivation or ion migration blocking layers, dimensional reduction to two-dimensional phases or nanoparticles, grain size engineering or fabrication of single-crystal materials^{7–10}. Despite the progress to date, obtaining materials and devices with both an optimal optoelectronic performance and a long lifetime under working conditions remains challenging.

Among the factors that cause degradation of perovskite materials and devices, humidity has been recognized as a severe and irreversible source of damage. To achieve high-performance optoelectronic devices, the amount of water involved in the material synthesis and exposed to perovskite active layers in devices has to be strictly controlled. This is, however, not the case in a recent publication, where Liu et al. fabricated the lead bromide perovskite nanoparticles that show excellent stability and high luminescence performance by deliberately introducing a large amount of water¹¹.

The fabricated methylamino lead bromide perovskite (MAPbBr₃) samples are reaction products of ammonium ion modified MAPbBr₃ and water, and are composed of MAPbBr₃ nanoparticles encapsulated in PbBr(OH) matrix (Fig. 1). The PbBr(OH) encapsulation improves the material stability and luminescent behavior for several reasons: first, it acts as a blocking layer to prevent ions (e.g., MA⁺) from escaping to the air or migrating among grains; second, it can passivate nonradiative defects on the perovskite surface (e.g., bromine vacancy V_{Br}) effectively; third, it will confine electron and hole states to enhance oscillator strength and intensity of optical transition; finally, it provides protection by isolating MAPbBr₃ from sources of degradation, such as H₂O/O₂. Compared with the MAPbBr₃ synthesized by the normal procedure, the fabricated samples exhibit a significantly enhanced photoluminescence quantum yield (PLQY) from about 2.5% to 71.54%. Meanwhile the PLQY of the samples decreases to only ~90% of its initial

Correspondence: Lijun Zhang (lijun_zhang@jlu.edu.cn)

¹State Key Laboratory of Integrated Optoelectronics, Key Laboratory of Automobile Materials of MOE and College of Materials Science and Engineering, Jilin University, Changchun 130012, China

© The Author(s) 2020

Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>.

value after one-year storage in aqueous solution. The samples show good stability under humid, high-temperature, and illumination conditions.

The synthesis approach that involves water is universal to halide perovskites with different A-site cations. Moreover, it is facile and may be extended to large-scale production. This offers a new and feasible strategy to fabricate highly stable and luminescent halide perovskites and indicates that there are remaining options to be explored to improve the stability of this family of materials. Future research may be directed at optimizing the profile of PbBr(OH) encapsulation layers and the interface between them and halide perovskites to enable more efficient charge carrier injection, which may improve the performance of the materials and devices further.

Acknowledgements

This work is supported by the National Natural Science Foundation of China (Grant No. 61722403).

Conflict of interest

The authors declare that they have no conflict of interest.

Published online: 19 June 2020

References

1. Stranks, S. D. & Snaith, H. J. Metal-halide perovskites for photovoltaic and light-emitting devices. *Nat. Nanotechnol.* **10**, 391–402 (2015).
2. Miyasaka, T. et al. Perovskite solar cells: can we go organic-free, lead-free, and dopant-free? *Adv. Energy Mater.* **10**, 1902500 (2020).
3. Xiao, Z. W., Song, Z. N. & Yan, Y. F. From lead halide perovskites to lead-free metal halide perovskites and perovskite derivatives. *Adv. Mater.* **31**, 1803792 (2019).
4. Xu, Q. L. et al. Perovskite solar absorbers: materials by design. *Small Methods* **2**, 1700316 (2018).
5. Park, N. G. et al. Towards stable and commercially available perovskite solar cells. *Nat. Energy* **1**, 16152 (2016).
6. Snaith, H. J. Present status and future prospects of perovskite photovoltaics. *Nat. Mater.* **17**, 372–376 (2018).
7. Cho, H. et al. Improving the stability of metal halide perovskite materials and light-emitting diodes. *Adv. Mater.* **30**, 1704587 (2018).
8. Zou, Y. et al. Recent progress toward perovskite light-emitting diodes with enhanced spectral and operational stability. *Mater. Today Nano* **5**, 100028 (2019).
9. Domanski, K. et al. Systematic investigation of the impact of operation conditions on the degradation behaviour of perovskite solar cells. *Nat. Energy* **3**, 61–67 (2018).
10. Boyd, C. C. et al. Understanding degradation mechanisms and improving stability of perovskite photovoltaics. *Chem. Rev.* **119**, 3418–3451 (2019).
11. Liu, K. K. et al. Water-induced MAPbBr₃@PbBr(OH) with enhanced luminescence and stability. *Light. Sci. Appl.* **9**, 44 (2020).