SCIENTIFIC REPORTS

There are amendments to this paper

OPEN

Entanglement Availability Differentiation Service for the Quantum Internet

Laszlo Gyongyosi^{1,2,3} & Sandor Imre²

Received: 29 January 2018
Accepted: 14 June 2018
Published online: 13 July 2018

A fundamental concept of the quantum Internet is quantum entanglement. In a quantum Internet scenario where the legal users of the network have different priority levels or where a differentiation of entanglement availability between the users is a necessity, an entanglement availability service is essential. Here we define the entanglement availability differentiation (EAD) service for the quantum Internet. In the proposed EAD framework, the differentiation is either made in the amount of entanglement with respect to the relative entropy of entanglement associated with the legal users, or in the time domain with respect to the amount of time that is required to establish a maximally entangled system between the legal parties. The framework provides an efficient and easily-implementable solution for the differentiation of entanglement availability in experimental quantum networking scenarios.

In the quantum Internet^{1,2}, one of the most important tasks is to establish entanglement^{1,3–11} between the legal parties^{12–16} so as to allow quantum communication beyond the fundamental limits of point-to-point connections^{17–19}. For the problem of entanglement distribution in quantum repeater networks several methods^{8,11–16}, and physical approaches have been introduced^{2,20–46}. The current results are mainly focusing on the physical-layer of the quantum transmission^{6–10}, implementations of entanglement swapping and purification, or on the optimization of quantum memories and quantum error correction in the repeater nodes^{2,20–43}. However, if the legal users of the quantum network are associated with different priority levels, or if a differentiation of entanglement availability between the users is a necessity in a multiuser quantum network, then an efficient and easily implementable entanglement availability service is essential.

In this work, we define the *entanglement availability differentiation* (EAD) service for the quantum Internet. We introduce differentiation methods, Protocols 1 and 2, within the EAD framework. In Protocol 1, the differentiation is made in the amount of entanglement associated with the legal users. The metric used for the quantization of entanglement is the relative entropy of entanglement function^{47–49}. In Protocol 2, the differentiation is made in the amount of time that is required to establish a maximally entangled system between the legal parties.

The EAD framework contains a classical phase (Phase 1) for the distribution of timing information between the users of the quantum network. Phase 2 consists of all quantum transmission and unitary operations. In Phase 2, the entanglement establishment is also performed between the parties according to the selected differentiation method.

The entanglement distribution phase of EAD utilizes Hamiltonian dynamics, which allows very efficient practical implementation for both the entanglement establishment and the differentiation of entanglement availability. Using the Hamiltonian dynamics approach as a core protocol of Step 2 of the EAD framework, the entanglement differentiation method requires only unitary operations at the transmitter and requires no entanglement transmission. The application time of the unitaries can be selected as arbitrarily small in the transmitter to achieve an efficient practical realization. The proposed EAD framework is particularly convenient for experimental quantum networking scenarios, quantum communication networks, and future quantum internet.

The novel contributions of our manuscript are as follows:

¹School of Electronics and Computer Science, University of Southampton, Southampton, SO17 1BJ, UK. ²Department of Networked Systems and Services, Budapest University of Technology and Economics, Budapest, H-1117, Hungary. ³MTA-BME Information Systems Research Group, Hungarian Academy of Sciences, Budapest, H-1051, Hungary. Correspondence and requests for materials should be addressed to L.G.Y. (email: l.gyongyosi@soton.ac.uk)

Figure 1. Framework of the entanglement differentiation service in a multiuser quantum network. **(a)** Phase 1. Classical transmission. The $\mathcal{E}$ encoder unit distributes the timing information for the legal transmit users $U_1, \dots, U_K$ and receiver users $B_1, \dots, B_K$ via a classical channel. **(b)** Phase 2. Quantum transmission. The users apply the core protocol for the entanglement establishment. Then, using the received timing information the transmit users $U_1, \dots, U_K$ apply the local unitaries for time $T_{U_1}, \dots, T_{U_K}$.

- We define the entanglement availability differentiation (EAD) service for the quantum Internet.
- The entanglement availability differentiation is achieved via Hamiltonian dynamics between the users of the quantum network.
- The EAD framework can differentiate in the amount of entanglement with respect to the relative entropy of entanglement associated to the legal users (Protocol 1), and also in the time domain with respect to the amount of time that is required to establish a maximally entangled system (Protocol 2) between the legal parties.
- The framework provides an efficient and easily-implementable solution for the differentiation of entanglement availability in experimental quantum networking scenarios.

This paper is organized as follows. Section 2 defines the framework for the proposed entanglement differentiation methods. Section 3 discusses the entanglement differentiation schemes. Finally, Section 4 concludes the results. Supplemental information is included in the Appendix.

System Model

The proposed EAD service allows differentiation in the amount of entanglement shared between the users or the amount of time required for the establishment of maximally entangled states between the users. The defined service requires no entanglement transmission to generate entanglement between the legal parties. The differentiation service consists of two phases: a classical transmission phase (Phase 1) to distribute side information for the entanglement differentiation and a quantum transmission phase (Phase 2), which covers the transmission of unentangled systems between the users and the application of local unitary operations to generate entanglement between the parties.

The proposed entanglement availability differentiation methods are detailed in Protocol 1 and Protocol 2. The protocols are based on a core protocol (Protocol 0) that utilizes Hamiltonian dynamics for entanglement distribution in quantum communication networks (see Section A.1 in the Supplementary information). The aim of the proposed entanglement differentiation protocols (Protocol 1 and Protocol 2) is different from the aim of the core protocol, since Protocol 0 serves only the purpose of entanglement distribution, and allows no entanglement differentiation in a multiuser quantum network. Protocol 0 is used only in the quantum transmission phase and has no any relation with a classical communication phase.

Classical Transmission Phase. In the classical transmission phase (Phase 1), the timing information of the local Hamiltonian operators are distributed among the legal parties by an $\mathcal{E}$ encoder unit. The content of the timing information depends on the type of entanglement differentiation method. The Hamiltonian operators will be applied in the quantum transmission phase (Phase 2) to generate entangled systems between the users. Since each types of entanglement differentiation requires the distribution of different timing information between the users, the distribution of classical timing information will be discussed in detail in Section 3.

Quantum Transmission Phase. The quantum transmission phase (Phase 2) utilizes a core protocol for the entanglement distribution protocol of the EAD framework. The core protocol requires no entanglement transmission for the entanglement generation, only the transmission of an unentangled quantum system (i.e., separable state^{11–16}) and the application of a unitary operation for a well-defined time in the transmit user. The core protocol of the quantum transmission phase for a user-pair is summarized in Protocol 0. It assumes the use of redundant quantum parity code⁸ for the encoding (actual coding scheme can be different). For a detailed description of Protocol 0, see Section A.1 in the Supplementary information.

Framework. In our multiuser framework, the quantum transmission phase is realized by the core protocol of Phase 2; however, time t of the Hamiltonian operator is selected in a different way among the users, according to the selected type of differentiation. For an i -th user U_i , the application time of the local unitary is referred to as T_{U_i} . Without loss of generality, the i -th transmit user is referred to as U_i and the i -th receiver user is B_i .

In the system model, the user pairs can use the same physical quantum link, therefore in the physical layer the users can communicate over the same quantum channel. On the other hand, in a logical layer representation of the protocols, the communication between the user pairs formulate logically independent channels.

The method of entanglement differentiation service is summarized in Fig. 1. The basic model consists of two phases: distribution of timing information over classical links (Fig. 1(a)) and the transmission of quantum systems and the application of local unitary operations (Fig. 1(b)).

Protocol 0. Core Protocol.

Step 1. Alice (transmitter node) and Bob (receiver node) agree on a time t , in which they want to establish entanglement between subsystems A and B . Alice generates a separable initial system AB , with no entanglement between A and B as

$$\rho_{AB} = \frac{1}{2} |\psi_+\rangle \langle \psi_+| + \frac{1}{2} |\phi_+\rangle \langle \phi_+|, \quad (1)$$

where $|\psi_+\rangle = \frac{1}{\sqrt{2}} (|01\rangle + |10\rangle)$, $|\phi_+\rangle = \frac{1}{\sqrt{2}} (|00\rangle + |11\rangle)$. Alice encodes subsystem B , $|\phi_B\rangle = \alpha|0\rangle + \beta|1\rangle$ via an (m, n) redundant quantum parity code as

$$|\delta_B\rangle^{(m,n)} = \alpha |\chi_+\rangle_1^{(m)} \dots |\chi_+\rangle_n^{(m)} + \beta |\chi_-\rangle_1^{(m)} \dots |\chi_-\rangle_n^{(m)}, \quad (2)$$

where $|\chi_\pm\rangle^{(m)} = |0\rangle^{\otimes m} \pm |1\rangle^{\otimes m}$, and sends subsystem B to Bob through the network of n intermediate transfer nodes.

Each intermediate transfer nodes $\mathcal{N}_{1\dots n}$ receives and retransmits $|\delta_B\rangle^{(m,n)}$. Bob receives $|\delta_B\rangle^{(m,n)}$ and decodes it.

Step 2. Alice prepares a system C , denoted by density $\rho_C = \frac{1}{2} (I + s\sigma^x)$ which is completely uncorrelated from ρ_{AB} , where I is the identity operator, σ^x is the Pauli X matrix, while s is a constant. Alice applies a unitary U'_{AC} on A and C , which produces the initial system ABC with no entanglement between A and B as

$$\rho_{ABC} = U'_{AC} \rho_{AB} \rho_C (U'_{AC})^\dagger = \frac{1}{2} |\psi_+\rangle \langle \psi_+| |+\rangle \langle +| + \frac{1}{2} |\phi_+\rangle \langle \phi_+| |-\rangle \langle -|, \quad (3)$$

where $|\pm\rangle = \frac{1}{\sqrt{2}} (|0\rangle \pm |1\rangle)$.

Step 3. Alice applies the unitary U_{AC} on subsystem AC for a time t , as

$$U_{AC} = \exp(-iH_{AC}t) = \cos(t)I - i\sin(t)\sigma_A^x\sigma_C^x, \quad (4)$$

where

$$H_{AC} = \sigma_A^x\sigma_C^x \quad (5)$$

is the Hamiltonian with energy E_{AC}

$$E_{AC} = \frac{1}{2} \hbar 2\pi \left(\frac{1}{4t}\right), \quad (6)$$

where $\hbar$ is the reduced Planck constant, which results in the maximally entangled AB system with probability $p = 1$ as

$$\sigma_{AB} = \frac{1}{2} (|\psi_+\rangle - i|\phi_+\rangle)(\langle \psi_+| + i\langle \phi_+|). \quad (7)$$

Methods of Entanglement Availability Differentiation

The EAD service defines different types of differentiation. The differentiation can be achieved in the amount of entanglement in terms of the relative entropy of entanglement between the users (*Protocol 1*: differentiation in the amount of entanglement). In this method, all users have knowledge of a global oscillation period⁴¹ of time for the application of their local unitaries, but the users will get different amounts of entanglement as a result.

The differentiation is also possible in the amount of time that is required to establish a maximally entangled system between the users (*Protocol 2*: differentiation in the time domain). In this method, all users get a maximally entangled system as a result; however, the time that is required for the entanglement establishment is variable for the users, and there is also no global oscillation period of time.

Differentiation in the Amount of Entanglement. The differentiation of the entanglement amount between the users allows us to weight the entanglement amount between the users in terms of relative entropy of entanglement. Using the timing information distributed in Phase 1 between the K transmit users $U_1, \dots, U_K$

$$T_{U_i} = x_{U_i} + (\pi/4), \quad i = 1, \dots, K, \quad (8)$$

where

$$x_{U_i} \in [-(\pi/4), (\pi/4)], \quad (9)$$

for an i -th transmit user U_i , the protocol generates an initial system ABC , transmits separable B to receiver B_i and applies the local unitary U_{AC} on subsystem AC for time T_{U_i} (using the core protocol of Phase 2). Depending on the selected T_{U_i} , the resulting AB subsystem between users U_i and B_i contains the selected amount of entanglement,

$$E^{(T_{U_i})}(U_i : B_i) \leq 1. \quad (10)$$

Relative Entropy of Entanglement. In the proposed service framework, the amount of entanglement is quantified by the $E(\cdot)$ relative entropy of entanglement function. By definition, the $E(\rho)$ relative entropy of entanglement function of a joint state ρ of subsystems A and B is defined by the $D(\cdot \| \cdot)$ quantum relative entropy function, without loss of generality as

$$E(\rho) = \min_{\rho_{AB}} D(\rho \| \rho_{AB}) = \min_{\rho_{AB}} \text{Tr}(\rho \log \rho) - \text{Tr}(\rho \log(\rho_{AB})), \quad (11)$$

where ρ_{AB} is the set of separable states $\rho_{AB} = \sum_{i=1}^n p_i \rho_{A,i} \otimes \rho_{B,i}$.

Differentiation Service. The Phases 1 and 2 of the method of entanglement amount differentiation (Protocol 1) are as included in Protocol 1.

Protocol 1. Differentiation in the Amount of Entanglement.

- Step 1.** Let $U_i, i = 1, \dots, K$ be the set of transmit users, and $B_i, i = 1, \dots, K$ are the receiver users. Distribute the $T_{U_i} = x_{U_i} + (\pi/4), i = 1, \dots, K$, where $x_{U_i} \in [- (\pi/4), (\pi/4)]$, timing information via an encoder unit $\mathcal{E}$ between all transmit users using a classical authenticated channel (Phase 1).
- Step 2.** In the transmit user U_i , generate the initial system ABC , transmit separable B to receiver B_i , and apply the local unitary U_{AC} on subsystem AC for time T_{U_i} (Core protocol of Phase 2 between the users).
- Step 3.** The resulting AB subsystem after total time $T = T_{U_i}$ between users U_i and B_i contains entanglement $E^{(T_{U_i})}(U_i : B_i) = \sin^2(2(\frac{\pi}{4} + x_{U_i}))$.
-

Description. In the quantum transmission phase, the entanglement oscillation in AB is generated by the energy E of the Hamiltonian H^{11} . This oscillation has a period of time T_π , which exactly equals to $4t$,

$$T_\pi = 4t, \quad (12)$$

where t is determined by Alice and Bob. In other words, time t identifies $\pi/4$, where π is the oscillation period. Therefore, in Protocol 1, the density σ_{ABC} of the final ABC state is as

$$\begin{aligned} \sigma_{ABC} &= |\varphi(t)\rangle\langle\varphi(t)|_{ABC} = U\rho_0 U^\dagger \\ &= \frac{1}{2}(U_{AC}|\psi_+\rangle\langle\psi_+| + |U_{AC}^\dagger) + \frac{1}{2}(U_{AC}|\phi_+\rangle\langle\phi_+| - |U_{AC}^\dagger), \end{aligned} \quad (13)$$

where $|\varphi(t)\rangle_{ABC}$ at time t is evaluated as

$$\begin{aligned} |\varphi(t)\rangle_{ABC} &= \frac{1}{\sqrt{2}}(\cos(t)(|\psi_+\rangle|+) - i \sin(t)(|\phi_+\rangle|+)) \\ &\quad + \frac{1}{\sqrt{2}}(\cos(t)(|\phi_+\rangle|-) + i \sin(t)(|\psi_+\rangle|-)) \\ &= \frac{1}{\sqrt{2}}(\cos(t)(|\psi_+\rangle) - i \sin(t)(|\phi_+\rangle))|+ \rangle \\ &\quad + \frac{1}{\sqrt{2}}(\cos(t)(|\phi_+\rangle) + i \sin(t)(|\psi_+\rangle))|- \rangle \end{aligned} \quad (14)$$

which at T_{U_i} (see (8)) of user U_i for a given x_{U_i} is evaluated as

$$\begin{aligned} |\phi(T_{U_i})\rangle_{ABC} &= \frac{1}{\sqrt{2}}\left(\cos\left(\frac{\pi}{4} + x_{U_i}\right)(|\psi_+\rangle) - i \sin\left(\frac{\pi}{4} + x_{U_i}\right)(|\phi_+\rangle)\right)|+ \rangle \\ &\quad + \frac{1}{\sqrt{2}}\left(\cos\left(\frac{\pi}{4} + x_{U_i}\right)(|\phi_+\rangle) + i \sin\left(\frac{\pi}{4} + x_{U_i}\right)(|\psi_+\rangle)\right)|- \rangle \\ &= \frac{1}{\sqrt{2}}\left[\left(\frac{1}{\sqrt{2}}(\cos(x_{U_i})) - \frac{1}{\sqrt{2}}(\sin(x_{U_i}))\right)(|\psi_+\rangle)\right]|+ \rangle \\ &\quad - i\left(\frac{1}{\sqrt{2}}(\cos(x_{U_i})) + \frac{1}{\sqrt{2}}(\sin(x_{U_i}))\right)(|\phi_+\rangle)\right]|+ \rangle \\ &\quad + \frac{1}{\sqrt{2}}\left[\left(\frac{1}{\sqrt{2}}(\cos(x_{U_i})) - \frac{1}{\sqrt{2}}(\sin(x_{U_i}))\right)(|\phi_+\rangle)\right)|- \rangle \\ &\quad + i\left(\frac{1}{\sqrt{2}}(\cos(x_{U_i})) + \frac{1}{\sqrt{2}}(\sin(x_{U_i}))\right)(|\psi_+\rangle)\right]|- \rangle, \end{aligned} \quad (15)$$

where the sign change on $U_{AC}(|\phi_+\rangle|-\rangle)$ is due to the $|-\rangle$ eigenstate on C , and where

$$\begin{aligned} & \frac{1}{\sqrt{2}}(\cos(x_{U_i})) - \frac{1}{\sqrt{2}}(\sin(x_{U_i}))(|\phi_+\rangle) + i\left(\frac{1}{\sqrt{2}}(\cos(x_{U_i})) + \frac{1}{\sqrt{2}}(\sin(x_{U_i}))\right)(|\psi_+\rangle) \\ & = i\left(\frac{1}{\sqrt{2}}(\cos(x_{U_i})) + \frac{1}{\sqrt{2}}(\sin(x_{U_i}))\right)(|\psi_+\rangle) - i\left(\frac{1}{\sqrt{2}}(\cos(x_{U_i})) - \frac{1}{\sqrt{2}}(\sin(x_{U_i}))\right)(|\phi_+\rangle). \end{aligned} \quad (16)$$

Thus, up to the global phase, both states are the same.

Therefore, the $|\varphi(T_{U_i})\rangle_{ABC}$ system state of ABC at T_{U_i} is yielded as

$$|\varphi(T_{U_i})\rangle_{ABC} = \frac{1}{\sqrt{2}}|\xi(T_{U_i})\rangle_{AB}|+\rangle + \frac{1}{\sqrt{2}}|\xi(T_{U_i})\rangle_{AB}|-\rangle, \quad (17)$$

therefore, the resulting time AB state at $t = T_{U_i} = x_{U_i} + (\pi/4)$ and $x_{U_i} \neq 0$, $|\xi(T_{U_i})\rangle_{AB}$ is a non-maximally entangled system

$$\begin{aligned} |\xi(T_{U_i})\rangle_{AB} &= \frac{1}{\sqrt{2}}(\cos(x_{U_i})) + \frac{1}{\sqrt{2}}(\sin(x_{U_i}))(|\psi_+\rangle) \\ &\quad - i\left(\frac{1}{\sqrt{2}}(\cos(x_{U_i})) - \frac{1}{\sqrt{2}}(\sin(x_{U_i}))\right)(|\phi_+\rangle), \end{aligned} \quad (18)$$

with entanglement between user U_i and B_i as

$$E^{(T_{U_i})}(U_i: B_i) = \sin^2\left(2\left(\frac{\pi}{4} + x_{U_i}\right)\right). \quad (19)$$

Differentiation in the Time Domain. In the time domain differentiation service, a transmit user U_i generates the initial system ABC , transmits separable B to receiver B_i , and applies the local unitary U_{AC} on subsystem AC for time $T_{U_i}(\pi/4)$ (using the core protocol of Phase 2). Using the oscillation period $T_{\pi}(U_i: B_i)$ distributed in Phase 1, the resulting AB subsystem after total time

$$T = T_{U_i}(\pi/4) = T_{\pi}(U_i: B_i)/4 \quad (20)$$

between users U_i and B_i , $i = 1, \dots, K$ is a maximally entangled system, $E^{(T_{\pi})}(U_i: B_i) = 1$, for all i .

Differentiation Service. The Phases 1 and of the time domain differentiation method (Protocol 2) are as included in Protocol 2.

Protocol 2. Differentiation in Time Domain.

Step 1. Let $U_i, i = 1, \dots, K$ be the set of transmit users, and $B_i, i = 1, \dots, K$ are the receiver users. Let $T_{\pi}(U_i: B_i)$ be the oscillation time selected for user pairs U_i and B_i , and let $T_{U_i}(\pi/4)$ be defined as

$$T_{U_i}\left(\frac{\pi}{4}\right) = \frac{T_{\pi}(U_i: B_i)}{4}. \quad (21)$$

For all i , distribute the oscillation period of time $T_{\pi}(U_i: B_i)$ information via an encoder unit $\mathcal{E}$ between U_i and B_i (Phase 1).

Step 2. In the transmit user U_i , generate the initial system ABC , transmit separable B to receiver B_i , and apply the local unitary U_{AC} on subsystem AC for time $T_{U_i}(\pi/4)$ (Core protocol of Phase 2 between the users).

Step 3. The resulting AB subsystem after total time $T = T_{U_i}(\pi/4) = T_{\pi}(U_i: B_i)/4$ between users U_i and B_i is a maximally entangled system, $E^{(T_{\pi})}(U_i: B_i) = 1$, for all i .

Description. Let us focus on a particular ABC of users U_i and B_i . The same results apply for all users of the network.

After the steps of Protocol 2, the density σ_{ABC} of the final ABC state is as

$$\begin{aligned} \sigma_{ABC} &= |\varphi(t)\rangle\langle\varphi(t)|_{ABC} = U\rho_0U^\dagger \\ &= \frac{1}{2}(U_{AC}|\psi_+\rangle\langle\psi_+| + |+\rangle\langle+|U_{AC}^\dagger) + \frac{1}{2}(U_{AC}|\phi_+\rangle\langle\phi_+| - |-\rangle\langle-|U_{AC}^\dagger), \end{aligned} \quad (22)$$

where $|\phi(t)\rangle_{ABC}$ at t is evaluated as

Figure 2. Entanglement differentiation service via Hamiltonian dynamics in a multiuser environment. **(a)** Protocol 1. Each user gives a different amount of entanglement $E(U_i; B_i) \leq 1$ at a global period of time T_π . The differentiation is made in the amount of entanglement (relative entropy of entanglement) by applying the local unitaries for time T_{U_i} for $U_i, i = 1, \dots, K$. User U_5 has the highest priority thus the user gets a maximally entangled system, user U_3 is the lowest priority user with and associated with a low amount of entanglement. **(b)** Protocol 2. All users are assigned with a maximally entangled system, $E(U_i; B_i) = 1$, and the differentiation is made in the time domain. For users $U_i, B_i, i = 1, \dots, K$ a particular period of time $T_\pi(U_i; B_i)$ is assigned, and each local unitary is applied for $T_{U_i}(\pi/4) = T_\pi(U_i; B_i)/4$ time t to achieve maximally entangled states between the parties. User U_5 has the highest priority thus the user associated with the shortest time period, user U_3 is the lowest priority user with a long time period for the generation of a maximally entangled system.

$$\begin{aligned}
 |\varphi(t)\rangle_{ABC} &= \frac{1}{\sqrt{2}}(U_{AC}(|\psi_+\rangle|+\rangle) + U_{AC}(|\phi_+\rangle|-\rangle)) \\
 &= \frac{1}{\sqrt{2}}(\cos(t)\left(\frac{1}{2}(|010\rangle + |011\rangle + |100\rangle + |101\rangle)\right) \\
 &\quad + \cos(t)\left(\frac{1}{2}(|000\rangle - |001\rangle + |110\rangle - |111\rangle)\right) \\
 &\quad - i \sin(t)\left(\frac{1}{2}(|111\rangle + |110\rangle + |001\rangle + |000\rangle)\right) \\
 &\quad + i \sin(t)\left(\frac{1}{2}(|101\rangle - |100\rangle + |011\rangle - |010\rangle)\right)) \\
 &= \frac{1}{\sqrt{2}}(\cos(t)(|\psi_+\rangle|+\rangle + |\phi_+\rangle|-\rangle) - i \sin(t)(|\phi_+\rangle|+\rangle - |\psi_+\rangle|-\rangle)) \\
 &= \frac{1}{\sqrt{2}}((\cos(t)(|\psi_+\rangle) - i \sin(t)(|\phi_+\rangle))|+\rangle \\
 &\quad + (\cos(t)(|\phi_+\rangle) + i \sin(t)(|\psi_+\rangle))|-\rangle),
 \end{aligned} \tag{23}$$

where the sign change on $U_{AC}(|\phi_+\rangle|-\rangle)$ is due to the $|-\rangle$ eigenstate on C .

Thus, at $t = \pi/4 = T_{U_i}(\pi/4)$, the system state is

$$\begin{aligned}
 |\varphi(T_{U_i}(\pi/4))\rangle_{ABC} &= \frac{1}{\sqrt{2}}(\cos(\pi/4)(|\psi_+\rangle|+\rangle + |\phi_+\rangle|-\rangle) \\
 &\quad - i \sin(\pi/4)(|\phi_+\rangle|+\rangle - |\psi_+\rangle|-\rangle)) \\
 &= \frac{1}{\sqrt{2}}\left(\frac{1}{\sqrt{2}}(|\psi_+\rangle|+\rangle + |\phi_+\rangle|-\rangle) - i\frac{1}{\sqrt{2}}(|\phi_+\rangle|+\rangle - |\psi_+\rangle|-\rangle)\right) \\
 &= \frac{1}{\sqrt{2}}\left[\left(\frac{1}{\sqrt{2}}(|\psi_+\rangle) - i\frac{1}{\sqrt{2}}(|\phi_+\rangle)\right)|+\rangle\right. \\
 &\quad \left.+\left(\frac{1}{\sqrt{2}}(|\phi_+\rangle) + i\frac{1}{\sqrt{2}}(|\psi_+\rangle)\right)|-\rangle\right],
 \end{aligned} \tag{24}$$

where

$$\frac{1}{\sqrt{2}}(|\phi_+\rangle + i|\psi_+\rangle) = i\left(\frac{1}{\sqrt{2}}(|\psi_+\rangle - i|\phi_+\rangle)\right); \tag{25}$$

Thus, up to the global phase both states are the same yielding relative entropy of entanglement between users U_i and B_i as

$$E^{(T_n)}(U_i; B_i) = 1 \quad (26)$$

with unit probability.

Comparative Analysis. The results of the proposed differentiation methods, Protocols 1 and 2, are compared in Fig. 2. Figure 2(a) illustrates the results of a differentiation in the entanglement quantity, while Fig. 2(b) depicts the results of the time-domain differentiation method.

Conclusions

Entanglement differentiation is an important problem in quantum networks where the legal users have different priorities or where differentiation is a necessity for an arbitrary reason. In this work, we defined the EAD service for the availability of entanglement in quantum Internet. In EAD, the differentiation is either made in the amount of entanglement associated with a legal user or in the amount of time that is required to establish a maximally entangled system. The EAD method requires a classical phase for the distribution of timing information between the users. The entanglement establishment is based on Hamiltonian dynamics, which allows the efficient implementation of the entanglement differentiation methods via local unitary operations. The method requires no entanglement transmission between the parties, and the application time of the unitaries can be selected as arbitrarily small via the determination of the oscillation periods to achieve an efficient practical realization. The EAD method is particularly convenient for practical quantum networking scenarios, quantum communication networks, and future quantum Internet.

Ethics statement. This work did not involve any active collection of human data.

Data accessibility statement. This work does not have any experimental data.

References

- Lloyd, S. *et al.* Infrastructure for the quantum Internet. *ACM SIGCOMM Computer Communication Review* **34**(5), 9–20 (2004).
- Kimble, H. J. The quantum Internet. *Nature* **453**, 1023–1030 (2008).
- Van Meter, R. *Quantum Networking*, John Wiley and Sons Ltd, ISBN 1118648927, 9781118648926 (2014).
- Gyongyosi, L., Imre, S. & Nguyen, H. V. A Survey on Quantum Channel Capacities. *IEEE Communications Surveys and Tutorials* **99**, 1, <https://doi.org/10.1109/COMST.2017.2786748> (2018).
- Pirandola, S. Capacities of repeater-assisted quantum communications, *arXiv:1601.00966* (2016).
- Imre, S., Gyongyosi, L. *Advanced Quantum Communications - An Engineering Approach*. Wiley-IEEE Press (New Jersey, USA), (2013).
- Gyongyosi, L., Imre, S. Entanglement-Gradient Routing for Quantum Networks, *Sci. Rep.*, Nature (2017).
- Munro, W. J., Stephens, A. M., Devitt, S. J., Harrison, K. A. & Nemoto, K. Quantum communication without the necessity of quantum memories. *Nature Photonics* **6**, 777–781 (2012).
- Van Meter, R., Ladd, T. D., Munro, W. J. & Nemoto, K. System Design for a Long-Line Quantum Repeater. *IEEE/ACM Transactions on Networking* **17**(3), 1002–1013 (2009).
- Van Meter, R., Satoh, T., Ladd, T. D., Munro, W. J. & Nemoto, K. Path Selection for Quantum Repeater Networks. *Networking Science* **3**(Issue 1-4), 82–95 (2013).
- Krisnanda, T., Zuppardo, M., Paternostro, M. & Paterek, T. Revealing non-classicality of unmeasured objects. *Phys. Rev. Lett.* **119**, 120402 (2017).
- Cubitt, T. S., Verstraete, F., Dur, W. & Cirac, J. I. Separable States Can Be Used To Distribute Entanglement. *Phys. Rev. Lett.* **91**, 037902 (2003).
- Kay, A. Resources for Entanglement Distribution via the Transmission of Separable States, *arXiv:1204.0366v4*. *Phys. Rev. Lett.* **109**, 080503 (2012).
- Chuan, T. K. *et al.* Quantum discord bounds the amount of distributed entanglement, *arXiv:1203.1268v3*. *Phys. Rev. Lett.* **109**, 070501 (2012).
- Streltsov, A., Kampermann, H. & Bruss, D. Quantum cost for sending entanglement. *Phys. Rev. Lett.* **108**, 250501 (2012).
- Park, J. & Lee, S. Separable states to distribute entanglement, *arXiv:1012.5162v2*. *Int. J. Theor. Phys.* **51**(2012), 1100–1110 (2010).
- Pirandola, S., Laurenza, R., Ottaviani, C. and Banchi, L. Fundamental limits of repeaterless quantum communications, *Nature Communications*, 15043, <https://doi.org/10.1038/ncomms15043> (2017).
- Pirandola, S. *et al.* Theory of channel simulation and bounds for private communication. *Quantum Sci. Technol.* **3**, 035009 (2018).
- Laurenza, R. & Pirandola, S. General bounds for sender-receiver capacities in multipoint quantum communications. *Phys. Rev. A* **96**, 032318 (2017).
- Jiang, L., Taylor, J. M., Nemoto, K. & Munro, W. J. Van Meter, R. and Lukin, M.D. Quantum repeater with encoding. *Phys. Rev. A* **79**, 032325 (2009).
- Xiao, Y. F. & Gong, Q. Optical microcavity: from fundamental physics to functional photonics devices. *Science Bulletin* **61**, 185–186 (2016).
- Zhang, W. *et al.* Quantum Secure Direct Communication with Quantum Memory. *Phys. Rev. Lett.* **118**, 220501 (2017).
- Biamonte, J. *et al.* Quantum Machine Learning. *Nature* **549**, 195–202 (2017).
- Lloyd, S. Mohseni, M. and Rebentrost, P. Quantum algorithms for supervised and unsupervised machine learning. *arXiv:1307.0411* (2013).
- Lloyd, S., Mohseni, M. & Rebentrost, P. Quantum principal component analysis. *Nature Physics* **10**, 631 (2014).
- Lloyd, S. The Universe as Quantum Computer, *A Computable Universe: Understanding and exploring Nature as computation*, H. Zenil ed., World Scientific, Singapore, *arXiv:1312.4455v1* (2013).
- Kok, P. *et al.* Linear optical quantum computing with photonic qubits. *Rev. Mod. Phys.* **79**, 135–174 (2007).
- Gisin, N. & Thew, R. Quantum Communication. *Nature Photon.* **1**, 165–171 (2007).
- Enk, S. J., Cirac, J. I. & Zoller, P. Photonic channels for quantum communication. *Science* **279**, 205–208 (1998).
- Briegleb, H. J., Dur, W., Cirac, J. I. & Zoller, P. Quantum repeaters: the role of imperfect local operations in quantum communication. *Phys. Rev. Lett.* **81**, 5932–5935 (1998).

31. Dur, W., Briegel, H. J., Cirac, J. I. & Zoller, P. Quantum repeaters based on entanglement purification. *Phys. Rev. A* **59**, 169–181 (1999).
32. Duan, L. M., Lukin, M. D., Cirac, J. I. & Zoller, P. Long-distance quantum communication with atomic ensembles and linear optics. *Nature* **414**, 413–418 (2001).
33. Van Loock, P. *et al.* Hybrid quantum repeater using bright coherent light. *Phys. Rev. Lett* **96**, 240501 (2006).
34. Zhao, B., Chen, Z. B., Chen, Y. A., Schmiedmayer, J. & Pan, J. W. Robust creation of entanglement between remote memory qubits. *Phys. Rev. Lett.* **98**, 240502 (2007).
35. Goebel, A. M. *et al.* Multistage Entanglement Swapping. *Phys. Rev. Lett.* **101**, 080403 (2008).
36. Simon, C. *et al.* Quantum Repeaters with Photon Pair Sources and Multimode Memories. *Phys. Rev. Lett.* **98**, 190503 (2007).
37. Tittel, W. *et al.* Photon-echo quantum memory in solid state systems. *Laser Photon. Rev.* **4**, 244–267 (2009).
38. Sangouard, N., Dubessy, R. & Simon, C. Quantum repeaters based on single trapped ions. *Phys. Rev. A* **79**, 042340 (2009).
39. Dur, W. & Briegel, H. J. Entanglement purification and quantum error correction. *Rep. Prog. Phys* **70**, 1381–1424 (2007).
40. Petz, D. *Quantum Information Theory and Quantum Statistics*, Springer-Verlag, Heidelberg, Hiv: 6. (2008).
41. Lloyd, S. Capacity of the noisy quantum channel. *Physical Rev. A* **55**, 1613–1622 (1997).
42. Shor, P. W. Scheme for reducing decoherence in quantum computer memory. *Phys. Rev. A* **52**, R2493–R2496 (1995).
43. Sheng, Y. B. & Zhou, L. Distributed secure quantum machine learning. *Science Bulletin* **62**, 1025–2019 (2017).
44. Bisztray, T. and Bacsardi, L. The Evolution of Free-Space Quantum Key Distribution, *InfoComm. Journal X*:(1) pp. 22–30. (2018).
45. Bacsardi, L. On the Way to Quantum-Based Satellite Communication. *IEEE Comm. Mag.* **51**(08), 50–55 (2013).
46. Lang, M. D. & Caves, C. M. Quantum Discord and the Geometry of Bell-Diagonal States. *Phys. Rev. Lett.* **105**, 150501 (2010).
47. Vedral, V., Plenio, M. B., Rippin, M. A. & Knight, P. L. Quantifying Entanglement. *Phys. Rev. Lett.* **78**, 2275–2279 (1997).
48. Vedral, V. & Plenio, M. B. Entanglement measures and purification procedures. *Phys. Rev. A* **57**, 1619–1633 (1998).
49. Vedral, V. The role of relative entropy in quantum information theory. *Rev. Mod. Phys.* **74**, 197–234 (2002).

Acknowledgements

L.G.Y. would like to thank Tomasz Paterek for useful discussions. This work was partially supported by the National Research Development and Innovation Office of Hungary (Project No. 2017-1.2.1-NKP-2017-00001), by the Hungarian Scientific Research Fund - OTKA K-112125 and in part by the BME Artificial Intelligence FIKP grant of EMMI (BME FIKP-MI/SC).

Author Contributions

L.G.Y. designed the protocol and wrote the manuscript. L.G.Y. and S.I. analyzed the results. All authors reviewed the manuscript.

Additional Information

Supplementary information accompanies this paper at <https://doi.org/10.1038/s41598-018-28801-3>.

Competing Interests: The authors declare no competing interests.

Publisher's note: Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>.

© The Author(s) 2018