OPEN

Author Correction: Implementation of an efficient linear-optical quantum router

Karol Bartkiewicz¹, Antonín Černoch¹ & Karel Lemr¹Correction to: *Scientific Reports* <https://doi.org/10.1038/s41598-018-31273-0>, published online 07 September 2018

In Figure 3, the height of the second bar is incorrect and should be 0.939 as indicated in Table 1.

The correct Figure 3 appears below as Figure 1.

Figure 1. Probability of observing the signal photon leaving the router by the first (lightgrey upper portion of the bar) or the second (red lower segment of the bar) output port. The horizontal axis labels indicate the state of the control qubits (OFF and ON) and the state of the signal photon. Black segments centered at the top of each red bar depict the uncertainties of probability estimation. The presented probabilities are corrected by noise subtraction.

Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>.

© The Author(s) 2020